



## 3-1/8" Hole Dozer™ Bi-Metal Hole Saw 49-56-0177



The Milwaukee bi-metal hole saw offering has been upgraded to a new product, Hole Dozer<sup>™</sup>. As of December 1, 2014 all Milwaukee bi-metal hole saws are now shipping as this upgraded product. During this transition period, please visit Milwaukee Tool for the most up to date images and information. Online retailers sites are not all currently up to date.

## OVERVIEW

Made in the USA, the Milwaukee® Hole Dozer™ Hole Saw features Rip Guard<sup>™</sup>, the strongest tooth form in the industry, backed by the Rip Guard<sup>™</sup> Limited Lifetime Tooth Break Warranty. Each tooth is built with more steel behind the cutting edge for added strength. The Rip Guard™ warranty on tooth breaks is a first for the hole saw industry. The added tooth strength along with 8% cobalt give added life to the teeth, allowing for increased productivity on the jobsite, as well as continued hole quality. The Hole Dozer™ includes Plug Jack<sup>™</sup>, an all access slot design that allows for full access during plug removal. The Plug Jack™ gives access lower into the cup for thick material and higher towards the teeth for thin material. With multiple positions to apply leverage and better plug access, Plug Jack™ increases productivity and eliminates wasted downtime between holes. For fast, tool-free change-outs, use Milwaukee's universal Quick-Change Arbors. 49-56-7210, 49-56-7240, 49-56-7250, and 49-56-9100.

## PRODUCT DETAILS

FEATURES	SPECIFICATIONS	
Rip Guard <sup>™</sup> , the strongest tooth form in the industry	Pack Qty	1 Pack
Rip Guard™ Limited Lifetime Tooth Break Warranty	Package Type	Hanging Container
Plug Jack <sup>™</sup> , an all access slot design for fast plug removal	Hole Diameter	3-1/8"
Bi-metal construction with 8% cobalt for increased wear resistance	Depth of Cut	1-5/8"
	RPM Mild Steel	110
	RPM Stainless Steel	55
	RPM Cast Iron	70
	RPM Aluminum	165
	Packaging	Clamshell
	Size	3.00 <b>3-1/8</b> "