

## BORE POLISHERS

Characteristics/Applications	Materials	Tool Selector
<ul style="list-style-type: none"> <li>Self-centers to interior of tubes</li> <li>Flush wall sanding for smooth operation</li> <li>Precise flap spacing ensures balance</li> <li>Ideal for deburring, sizing, and cleaning cylinders, tubes, and hydraulic fittings</li> </ul>	<ul style="list-style-type: none"> <li>Ferrous</li> <li>Non-Ferrous</li> <li>Stainless</li> <li>Plastics</li> <li>Exotics</li> </ul>	

### "X" WT. 60 GRIT & UNDER - A/O

SIZE	I.D.'S	GRIT	MAX RPM	PART #
<b>SK-305</b> STD. PKG. 10	3/4" TO 1"	60	25,000	39161
		80		39162
		120		39163
		180		39164
<b>SK-405</b> STD. PKG. 10	1" TO 1 1/2"	60	22,000	39165
		80		39166
		120		39117
		180		39167
<b>SK-410</b> STD. PKG. 10	1 1/2" TO 2"	60	20,000	39168
		80		39169
		120		39170
		180		39171
<b>SK-415</b> STD. PKG. 10	2 1/8" TO 2 1/2"	60	16,000	39172
		80		39173
		120		39174
		180		39175
<b>SK-420</b> STD. PKG. 10	2 1/2" TO 3"	60	15,000	39176
		80		39177
		120		39178
		180		39179
<b>SK-425</b> STD. PKG. 10	3 1/8" TO 4"	60	10,000	39180
		80		39181

### "T" WT. 80 GRIT & ABOVE - A/O

SIZE	I.D.'S	GRIT	MAX RPM	PART #
<b>SK-425</b> STD. PKG. 10	3 1/8" TO 4"	120	10,000	39182
		180		39183
				39184
<b>SK-810</b> STD. PKG. 10	2" TO 2 1/2"	60	16,000	39185
		80		39186
		120		39187
		180		39188
<b>SK-815</b> STD. PKG. 10	2 5/8" TO 3"	60	15,000	39189
		80		39190
		120		39191
		180		39192
<b>SK-820</b> STD. PKG. 10	3 1/8" TO 4"	60	10,000	39193
		80		39194
		120		39195
		180		39196
<b>SK-825</b> STD. PKG. 10	4 1/4" TO 5 1/4"	60	8,000	39197
		80		39198
		120		39199
		180		39200
<b>SK-830</b> STD. PKG. 10	5 1/4" TO 5 7/8"	60	8,000	39201
		80		39202
		120		39203




### BORE POLISHERS "X" WT. - ZIRC

STYLE	I.D.'S	GRIT	MAX RPM	PART #
<b>SK-305</b> STD. PKG. 10	3/4" TO 1"	60	25,000	46169
		80		46170
		120		46171
		180		46172
<b>SK-405</b> STD. PKG. 10	1" TO 1 1/2"	60	22,000	46173
		80		46174
		120		46175
		180		46176
<b>SK-410</b> STD. PKG. 10	1 1/2" TO 2"	60	20,000	46177
		80		46178
		120		46179
		180		46180

**Superior support**

Bore polishers self-center for flush wall sanding or deburring through holes.



STYLE	I.D.'S	GRIT	MAX RPM	PART #
<b>SK-415</b> STD. PKG. 10	2 1/8" TO 2 1/2"	60	16,000	17218
		80		17219
		120		17220
		180		17221
<b>SK-420</b> STD. PKG. 10	2 1/2" TO 3"	60	15,000	46181
		80		46182
		120		46183
		180		46184
<b>SK-820</b> STD. PKG. 10	3 1/8" TO 4"	60	10,000	46195
		80		46196
		120		46197
		180		46239

### LONGER SHANKS

STYLE	DESCRIPTION	THREAD	PART #
<b>SK-144</b>	1/4" X 4" LONG	1/4-20	39207
<b>SK-146</b>	1/4" X 6" LONG	1/4-20	39208
<b>SK-148</b>	1/4" X 8" LONG	1/4-20	39209

### MANDRELS — 1/4" SHANK

STYLE	DESCRIPTION	THREAD	PART #
<b>SK-3</b>	SK-305 SERIES	5/16-18	39204
<b>SK-4</b>	SK-4 SERIES	1/2-20	39205
<b>SK-8</b>	SK-8 SERIES	1/4-20	39206

Red Part Numbers Are Stock Items  
www.superiorabrasives.com

**Free!**  
**SAMPLES**

Phone: 800-235-9123 / Fax: 800-841-3441  
Quote Fax: 877-420-1952

Call for Details