

1/8" PIPELINE WHEELS



GENERAL PURPOSE

A24R PIPELINE

- Aluminum oxide grain
- Designed and manufactured to perform both cutting and light grinding

METAL Ferrous metals (steel, cast iron, etc.)



HIGH PERFORMANCE

SAIT Z-TECH™

- Tough zirconium grain
- High performance cutting and light grinding for the toughest applications

METAL Ferrous metals (iron, steel, welds)

STAINLESS Stainless steel, high tensile alloys



PREMIUM PERFORMANCE

SAITECH™ PIPELINE

- High performance, ceramic aluminum oxide grain
- Uniform, high-density grain structure is extremely durable and self-sharpening for long life and a cooler cut
- Manufactured with proprietary ceramic abrasive grain to outlast standard aluminum oxide wheels
- Long life combined with versatility for the pipeline industry

STAINLESS Stainless steel, high tensile alloys

METAL Ferrous metals (iron, steel, welds)



PREMIUM PERFORMANCE

THE ULTIMATE PIPELINE™

- Features our proprietary grain and bond system
- Fast, free-cutting with long-lasting life
- Premium performance cutting and light grinding for even the toughest applications

METAL Ferrous metals (iron, steel, welds)

STAINLESS Stainless steel, high tensile alloys

PIPELINE WIRE BRUSHES AVAILABLE ON PAGE 121




DIA	THICK	ARBOR	MAX RPM	QTY	A24R PIPELINE	SAIT Z-TECH™	SAITECH™ PIPELINE	ULTIMATE PIPELINE™
4"	1/8"	3/8"	13,500	25	22007	-	-	-
4"	1/8"	5/8"	13,500	25	22015	-	-	-
4-1/2"	1/8"	7/8"	13,300	25	22030	22620	22264	20020
4-1/2"	1/8"	5/8-11	13,300	10	22130	22630	22269	20120
5"	1/8"	7/8"	12,200	25	22040	22622	22274	20025
5"	1/8"	5/8-11	12,200	10	22140	22632	22279	20125
6"	1/8"	7/8"	10,200	25	22042	22623	-	20030
6"	1/8"	5/8-11	10,200	10	22046	22633	-	20130
7"	1/8"	7/8"	8,500	25	22055	22624	22284	20035
7"	1/8"	5/8-11	8,500	10	22052	22634	22289	20135
9"	1/8"	7/8"	6,600	25	22065	22626	22294	20040
9"	1/8"	5/8-11	6,600	10	22062	22636	22299	20140

TECH INFO

- Designed for both cutting and light grinding, eliminating the need for two separate wheels
- Ideal for root pass grinding
- All sizes reinforced with the highest quality fiberglass for maximum safety and performance
- Saitech™, manufactured with premium ceramic abrasive grain, is designed to outlast standard aluminum oxide wheels
- Our unique Super-Lock™ Hub combines both a mechanical locking system and chemical bond providing one of the safest, vibration-free designs in the industry


Reusable 5/8-11 adapter for use on Type 1 and Type 27 reinforced wheels with a 7/8 arbor, a maximum diameter of 5" and a wheel thickness of .045" to 1/8" available in accessories on Page 130. (Part #95055)



Type 27



5/8-11 Super-Lock™ Hub



Angle Grinder