



Soft Face Tips are color coded to indicate hardness. They won't mar painted or polished surfaces and won't gash, mushroom or chip. Vibration and rebound are highly reduced. Tapered tips thread directly into hammer head and seat in head well through friction fit.

#### Hardness Conversion Guide

	Super Soft	Soft	Medium	Tough	Med. Hard	Hard	Extra Hard
Soft Rubber	■	■					
Soft Lead		■					
Wood		■	■				
Rubber			■				
Rawhide			■	■	■	■	■
Brass			■				
Hardwood				■	■		
Plastic				■		■	
Lead				■	■		
Micarta						■	■
Fiber						■	■
Copper							■

#### Soft Face Hammer Tips

Product Number	Diameter, Inches	Thread Size	Hardness	Color Code	Weight, lbs.
69-141	1	1/4-20	Super Soft	Gray	0.04
69-142	1	1/4-20	Soft	Brown	0.04
69-143	1	1/4-20	Medium	Red	0.04
69-145	1	1/4-20	Tough	Green	0.05
69-146	1	1/4-20	Med. Hard	Cream	0.03
69-148	1	1/4-20	Hard	Black	0.04
69-149	1	1/4-20	Extra Hard	Yellow	0.04
69-151	1-1/2	5/16-18	Super Soft	Gray	0.09
69-152	1-1/2	5/16-18	Soft	Brown	0.09
69-153	1-1/2	5/16-18	Medium	Red	0.10
69-155	1-1/2	5/16-18	Tough	Green	0.10
69-156	1-1/2	5/16-18	Med. Hard	Cream	0.09
69-158	1-1/2	5/16-18	Hard	Black	0.11
69-159	1-1/2	5/16-18	Extra Hard	Yellow	0.11
69-161	2	3/8-16	Super Soft	Gray	0.21
69-162	2	3/8-16	Soft	Brown	0.20
69-163	2	3/8-16	Medium	Red	0.20
69-165	2	3/8-16	Tough	Green	0.21
69-166	2	3/8-16	Med. Hard	Cream	0.18
69-168	2	3/8-16	Hard	Black	0.23
69-169	2	3/8-16	Extra Hard	Yellow	0.23
69-171	2-1/2	7/16-14	Super Soft	Gray	0.34
69-172	2-1/2	7/16-14	Soft	Brown	0.35
69-173	2-1/2	7/16-14	Medium	Red	0.37
69-175	2-1/2	7/16-14	Tough	Green	0.37
69-176	2-1/2	7/16-14	Med. Hard	Cream	0.32
69-178	2-1/2	7/16-14	Hard	Black	0.39
69-179	2-1/2	7/16-14	Extra Hard	Yellow	0.40
69-181	3	1/2-13	Super Soft	Gray	0.59
69-182	3	1/2-13	Soft	Brown	0.58
69-183	3	1/2-13	Medium	Red	0.59
69-185	3	1/2-13	Tough	Green	0.62
69-186	3	1/2-13	Med. Hard	Cream	0.52
69-188	3	1/2-13	Hard	Black	0.65
69-189	3	1/2-13	Extra Hard	Yellow	0.66

Fed'l Spec. GGG-H-33a



#### "Powerdrive" Dead Blow Hammers, Fiberglass Handle

Shot-loaded head delivers up to 30% greater impact while eliminating rebound. Thermoplastic head material won't mar work and will last many times longer than conventional soft face tips, without mushrooming. Fiberglass handle shafts-made with continuous parallel strands reinforced with polyester plastic-are permanently epoxied to head. Special molded grip is immune to oils and solvents, and provides comfortable, non-slip action, while helping to absorb shock.

Product Number	Weight Class	Head Dia., Inches	Handle Length, Inches	Weight, lbs.
69-501	1 lb.	1-7/8	11	1.38
69-503	2 lb.	2-1/8	11-3/4	1.87
69-505	3 lb.	2-3/8	12-5/8	2.61
69-507	4 lb.	2-5/8	13	3.12

Fed'l Spec. GGG-H-33a



Always wear eye protection when near tools in use.