

1/2" Drive 12 Point Standard Length Sockets

EYE-D

Product Number	Opening Inches	Weight Lbs.	A Drive End	B Wrench End	C Overall Length	D Bolt Clearance	E Wrench Depth	F Length to Shoulder
12-112	3/8	0.09	0.860	0.600	1.455	0.281	0.400	0.705
12-114	7/16	0.10	0.860	0.670	1.455	0.281	0.400	0.705
12-116	1/2	0.11	0.860	0.748	1.455	0.344	0.400	0.705
12-118	9/16	0.12	0.860	0.812	1.455	0.406	0.400	0.705
12-119	19/32	0.13	0.860	0.860	1.455	0.375	0.450	
12-120	5/8	0.14	0.870	0.870	1.455	0.469	0.475	
12-121	21/32	0.15	0.930	0.930	1.455	0.469	0.475	
12-122	11/16	0.15	0.956	0.956	1.455	0.469	0.500	
12-124	3/4	0.20	1.037	1.037	1.455		0.800	
12-125	25/32	0.21	1.125	1.125	1.455		0.800	
12-126	13/16	0.21	1.125	1.125	1.455		0.800	
12-128	7/8	0.22	1.173	1.173	1.455		0.800	
12-130	15/16	0.27	1.256	1.256	1.496		0.827	
12-132	1	0.31	1.307	1.307	1.614		0.846	
12-134	1-1/16	0.43	1.410	1.410	1.614		0.900	
12-136	1-1/8	0.42	1.480	1.480	1.654		1.000	
12-138	1-3/16	0.49	1.563	1.563	1.710		1.000	
12-140	1-1/4	0.58	1.650	1.650	1.715		1.000	
12-142	1-5/16	0.76	1.750	1.750	2.125	1.062	0.850	
12-144	1-3/8	0.90	1.812	1.812	2.125	1.064	0.875	
12-146	1-7/16	0.99	1.938	1.938	2.187	1.064	0.907	
12-148	1-1/2	1.08	2.000	2.000	2.250	1.064	0.907	

ASME B107.1 Fed'I Spec. GGG-W-641e

1/2" Drive 6 Point Standard Length Sockets

EYE-D

Product Number	Opening Inches	Weight Lbs.	A Drive End	B Wrench End	C Overall Length	D Bolt Clearance	E Wrench Depth	F Length to Shoulder
12-012	3/8	0.10	0.860	0.600	1.455	0.281	0.400	0.705
12-014	7/16	0.10	0.860	0.670	1.455	0.281	0.400	0.705
12-016	1/2	0.12	0.860	0.748	1.455	0.266	0.400	0.705
12-018	9/16	0.13	0.860	0.812	1.455	0.328	0.400	0.705
12-020	5/8	0.14	0.870	0.870	1.455	0.375	0.480	
12-022	11/16	0.16	0.956	0.956	1.455	0.375	0.500	
12-024	3/4	0.19	1.037	1.037	1.455		0.800	
12-026	13/16	0.22	1.125	1.125	1.455		0.800	
12-028	7/8	0.23	1.173	1.173	1.455		0.800	
12-030	15/16	0.27	1.256	1.256	1.496		0.827	
12-032	1	0.33	1.307	1.307	1.614		0.846	
12-034	1-1/16	0.40	1.410	1.410	1.614		0.900	
12-036	1-1/8	0.44	1.480	1.480	1.654		1.000	
12-038	1-3/16	0.49	1.563	1.563	1.710		1.000	
12-040	1-1/4	0.58	1.650	1.650	1.715		1.000	
12-042	1-5/16	0.79	1.750	1.750	2.062	1.062	0.820	
12-044	1-3/8	0.89	1.812	1.812	2.125	1.062	0.960	
12-046	1-7/16	1.07	1.938	1.938	2.187	1.062	0.960	
12-048	1-1/2	1.17	2.000	2.000	2.250	1.062	0.960	

ASME B107.1 Fed'I Spec. GGG-W-641e

SAFETY NOTICE

METRIC AND FRACTIONAL SOCKET OPENINGS ARE NOT INTERCHANGEABLE.
 PLEASE SELECT THE APPROPRIATE OPENING SIZE FOR THE JOB AT HAND.



Always wear eye protection when near tools in use.