



1/2" Drive 12 Point Deep Sockets

Product Number	Opening Inches	Weight Lbs.	A Drive End	B Wrench End	C Overall Length	D Bolt Clearance	E Wrench Depth	F Length to Shoulder
12-312	3/8	0.21	0.860	0.600	3.185	0.297	0.500	0.810
12-314	7/16	0.23	0.860	0.670	3.185	0.297	0.500	0.810
12-316	1/2	0.27	0.860	0.737	3.185	0.480	0.520	0.810
12-318	9/16	0.27	0.860	0.812	3.185	0.540	0.520	0.810
12-320	5/8	0.25	0.860	0.860	3.205	0.625	1.200	
12-322	11/16	0.29	0.956	0.956	3.205	0.650	1.450	
12-324	3/4	0.42	1.037	1.037	3.205	0.650	1.700	
12-326	13/16	0.41	1.115	1.115	3.205	0.770	1.800	
12-328	7/8	0.48	1.173	1.173	3.205	0.770	1.800	
12-330	15/16	0.55	1.256	1.256	3.235	0.870	1.300	
12-332	1	0.63	1.307	1.307	3.235	0.870	1.300	
12-334	1-1/16	0.70	1.410	1.410	3.235	0.990	1.600	
12-336	1-1/8	0.75	1.490	1.490	3.235	1.053	1.600	
12-338	1-3/16	0.93	1.563	1.563	3.235	0.797	0.844	
12-340	1-1/4	1.29	1.687	1.687	3.235	0.922	0.875	
12-342	1-5/16	1.35	1.750	1.750	3.235	0.922	0.940	
12-344	1-3/8	1.40	1.812	1.812	3.218	1.060	1.125	
12-346	1-7/16	1.53	1.938	1.938	3.218	1.060	1.125	
12-348	1-1/2	1.68	2.000	2.000	3.218	1.060	1.125	

ASME B107.1 Fed'l Spec. GGG-W-641eI



1/2 " Drive 6 Point Deep Sockets

Product Number	Opening Inches	Weight Lbs.	A Drive End	B Wrench End	C Overall Length	D Bolt Clearance	E Wrench Depth	F Length to Shoulder
12-212	3/8	0.30	0.860	0.600	3.185	0.297	0.570	0.810
12-214	7/16	0.31	0.860	0.670	3.185	0.297	0.500	0.810
12-216	1/2	0.31	0.860	0.737	3.185	0.480	0.500	0.810
12-218	9/16	0.29	0.860	0.812	3.185	0.540	0.500	0.810
12-220	5/8	0.28	0.860	0.860	3.205	0.625	1.200	
12-222	11/16	0.32	0.956	0.956	3.205	0.650	1.450	
12-224	3/4	0.40	1.037	1.037	3.205	0.650	1.700	
12-226	13/16	0.44	1.115	1.115	3.205	0.770	1.800	
12-228	7/8	0.50	1.173	1.173	3.205	0.770	1.800	
12-230	15/16	0.58	1.256	1.256	3.235	0.870	1.300	
12-232	1	0.65	1.307	1.307	3.235	0.870	1.300	
12-234	1-1/16	0.75	1.410	1.410	3.235	0.990	1.700	
12-236	1-1/8	0.81	1.490	1.490	3.235	1.053	1.700	
12-238	1-3/16	0.87	1.563	1.563	3.235	0.797	0.844	
12-240	1-1/4	1.31	1.687	1.687	3.235	0.922	0.875	
12-242	1-5/16	1.35	1.750	1.750	3.218	1.060	1.125	
12-244	1-3/8	1.42	1.812	1.812	3.218	1.060	1.125	
12-246	1-7/16	1.51	1.938	1.938	3.218	1.060	1.125	
12-248	1-1/2	1.73	2.000	2.000	3.218	1.060	1.125	

ASME B107.1 Fed'l Spec. GGG-W-641e

