

Jacobs® Thread Mounted - Medium Duty Model

- Jaws Center-Ground for Absolute Straightness and Alignment
- One-Piece Sleeve Eliminates Crack Between Driving Teeth Often Found in Other Designs
- Through-Hardened Sleeve Teeth, Plus Hardened Nose and Keyholes Provide Outstanding Wear Resistance
- Each Chuck 100% Inspected for Performance and Precision
- T.I.R. .004" Maximum at Half Capacity
- Models 0 and 1A are Smooth Sleeve.
- All Model 33 Plain Bearing Chucks are Hammer Capable.



Cat. No.	UPC No.	Packaging	Model No.	Min. Capacity	Max. Capacity	Mount	Key No.	Closed Length	Open Length	Sleeve Dia.	Product Weight	Shelf Pack Qty.
6204D	095456062047	Boxed	0B 5/16	0.0135 in	0.156 in	5/16-24	K0	1.53 in	1.17 in	0.85 in	0.13 lb	1
6208D	095456062085	Boxed	1B 3/8	0.040 in	0.250 in	3/8-24	K1	1.95 in	1.57 in	1.12 in	0.32 lb	1
6219D	095456062191	Boxed	2BA 3/8	0.040 in	0.375 in	3/8-24	K2	2.81 in	2.17 in	1.67 in	0.90 lb	1
6287D	095456062870	Boxed	33BA 1/2	0.08 in	0.500 in	1/2-20	K32	3.09 in	2.43 in	1.79 in	1.06 lb	1
6283D	095456062832	Boxed	33BA 3/8	0.08 in	0.500 in	3/8-24	K32	3.09 in	2.43 in	1.79 in	1.10 lb	1
6289D	095456062894	Boxed	33BA 5/8	0.08 in	0.500 in	5/8-16	K32	3.09 in	2.43 in	1.79 in	1.14 lb	1
31090	095456310902	Boxed	41BA 1/2	0.040 in	0.375 in	1/2-20	K30	2.50 in	2.05 in	1.43 in	0.60 lb	1
32282C	095456322820	Boxed	41BA 3/8	0.040 in	0.375 in	3/8-24	K30	2.50 in	2.05 in	1.43 in	0.60 lb	1
31138	095456311381	Boxed	41BA 3/8 - S	0.040 in	0.375 in	3/8-24	K30	2.50 in	2.05 in	1.43 in	0.62 lb	1

Jacobs® Thread Mounted - Light Duty Model

- Industrial Quality
- Through-Hardened Jaws Provide Hard, Durable Gripping Forces

Cat. No.	UPC No.	Packaging	Model No.	Min. Capacity	Max. Capacity	Mount	Key No.	Closed Length	Open Length	Sleeve Dia.	Product Weight	Shelf Pack Qty.
14946	095456149465	Boxed	24BA-3/8	0.063 in	0.50 in	3/8-24	KK	3.00 in	2.30 in	1.72 in	0.96 lb	1
14947	095456149472	Boxed	26BA-1/2	0.063 in	0.50 in	1/2-20	KK	3.00 in	2.30 in	1.72 in	0.94 lb	1