

Jacobs® High Precision Model Taper Mounted

- Precision Tested and Certified to 0.0016" T.I.R Max at Half Capacity
- Self-Tightening Feature Automatically Increases Gripping Force Proportional to Increased Torque to Prevent Tool Shank Slippage
- All Components Exposed to Wear are Completely Hardened to Maintain Accuracy and Extend Chuck Life
- Jacobs® Taper Mount Permits Use on a Wide Range of High Accuracy Drill Presses, Jig Borers, Milling Machines and Production Drilling Equipment
- 2Js Mount is a Short Taper



Cat. No.	UPC No.	Packaging	Model No.	Min. Capacity	Max. Capacity	Mount	Closed Length	Open Length	Sleeve Dia.	Product Weight	Shelf Pack Qty.
31121D	095456311213	Boxed	JKP 65-J1	0.012 in	0.255 in	1JT	2.76 in	2.44 in	1.28 in	0.69 lb	1
9679	095456096790	Boxed	JKP 80-J2S	0.012 in	0.315 in	2JS	2.91 in	2.64 in	1.46 in	0.98 lb	1
9681	095456096813	Boxed	JKP 100-J2	0.020 in	0.394 in	2JT	3.50 in	3.19 in	1.61 in	0.57 lb	1
9680	095456096806	Boxed	JKP 100-J33	0.020 in	0.394 in	33JT	3.50 in	3.19 in	1.61 in	0.57 lb	1
9683	095456096837	Boxed	JKP 130-J2	0.039 in	0.512 in	2JT	3.90 in	3.46 in	1.81 in	2.30 lb	1
9684	095456096844	Boxed	JKP 130-J6	0.039 in	0.512 in	6JT	3.90 in	3.46 in	1.81 in	2.20 lb	1
9682D	095456096820	Boxed	JKP 130-J33	0.039 in	0.512 in	33JT	3.90 in	3.46 in	1.81 in	2.22 lb	1
9685D	095456096851	Boxed	JKP 160-J6	0.118 in	0.630 in	6JT	4.21 in	3.74 in	2.17 in	2.82 lb	1

Jacobs® High Torque/High Precision Model

- Precision Tested and Certified to .0016" T.I.R. Maximum at Half Capacity
- For Use on CNC Machining Centers in Drilling, Boring, Counter-Boring and Milling Operations Requiring Heavy Penetration
- Furnished with Spanner Wrench to Allow the Application of Supplementary Gripping Torque. Light Tightening Increases Gripping Torque Up to 3 Times Higher Than Hand Tightening
- Resists Tool Loosening on High-Speed Machines with Right Hand Rotation and Instant Spindle Stop.
- 2Js Mount is a Short Taper



Cat. No.	UPC No.	Packaging	Model No.	Min. Capacity	Max. Capacity	Mount	Closed Length	Open Length	Sleeve Dia.	Product Weight	Shelf Pack Qty.
30533	095456305335	Boxed	JKT 100-J2	0.000 in	0.394 in	2JT	3.50 in	3.19 in	1.61 in	2.03 lb	1
30532D	095456305328	Boxed	JKT 100-J33	0.000 in	0.394 in	33JT	3.50 in	3.19 in	1.61 in	1.76 lb	1
30527	095456305274	Boxed	JKT 130-J2	0.039 in	0.512 in	2JT	3.90 in	3.46 in	1.81 in	0.00 lb	1
30529	095456305298	Boxed	JKT 130-J6	0.039 in	0.512 in	6JT	3.90 in	3.46 in	1.81 in	0.00 lb	1
30528	095456305281	Boxed	JKT 130-J33	0.039 in	0.512 in	33JT	3.90 in	3.46 in	1.81 in	0.00 lb	1
31122D	095456311220	Boxed	JKT65-J1	0.000 in	0.255 in	1JT	2.76 in	2.44 in	1.28 in	1.20 lb	1
30526D	095456305267	Boxed	JKT80-J2S	0.000 in	0.315 in	2JS	2.91 in	2.64 in	1.46 in	1.50 lb	1
30530D	095456305304	Boxed	JKT160-J6	0.118 in	0.630 in	6JT	4.21 in	3.74 in	2.17 in	0.00 lb	1