

## Drain Gasket

Item Code and Description

a. WP3401-DRN . . . Drain Gasket

General Product Description

- a. a rugged, flexible gasket with center hole for sealing the joint between a TrueDEK® Classic drain for tile and a TrueDEK® Classic shower foundation
- b. embed with TANK/10<sup>®</sup> waterproofing compound

#### Physical Characteristics

- a. one layer of nonwoven polypropylene fabric
- b. pre-punched hole fits TrueDEK® Classic drains
- c. color: gray
- d. dimensions: 13" x 13"
- e. hole diameter: 5<sup>9</sup>/16"
- f. thickness: .66mm
- g. material weight: 20 gsm

### Performance Characteristics

- a. a flexible fabric reinforcement for embedment around TrueDEK Classic drains
- b. absorbs and bonds with TANK/10<sup>®</sup> waterproofing compound
- c. remove all dirt, debris, and contaminants from surfaces prior to embedding gasket
- d. surfaces must be completely dry before embedding tape
- e. gasket is not designed as a wear surface; cover with tile, stone, or other appropriate material
- f. material safety data sheet available on request

#### Compliance

- a. ICC PMG-1248 lists compliance with:
  - 1. 2015, 2012 and 2009 International Residential Code® (IRC)
  - 2. 2015, 2012 and 2009 International Plumbing Code® (IPC)
  - 3. 2015, 2012 and 2009 Uniform Plumbing Code® (UPC)

CESPING

- 4. 2010 and 2005 National Plumbing Code of Canada (NPC)
- 5. ANSI A118.10-2008 American National Standard Specification for Load Bearing, Bonded, Waterproof Membranes for Thin-Set Ceramic Tile and Dimension Stone Installation
- 6. ICC-ES AC 115-2008 Acceptance Criteria for Waterproof membranes for Flooring and Shower Lining

#### Other Information

a. manufacturer warrants to the original owner of the property where product is installed that joint reinforcement tape and gaskets shall be free from defects in the material when properly applied for a period of five years



# Drain Gasket

ARC, Inc. 1715-743-2771 info@arcfirst.net



