


Wire and Cable Materials

Vinyl and Nylon Cloth Wire and Cable Labels (B-498 and B-499)



- **B-498 Repositionable Vinyl Cloth:** Adhesive and cloth backing offers excellent holding power, yet allow for clean removal and repositioning if necessary. Temp. range: -40° F to 175° F (-40° C to 70° C). UL recognized
- **B-499 Nylon Cloth Material:** Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized



| Fits Printers | Figure | Catalog # | B# | Material | Color | Approx. Wire Gauge | Label Width A Inch (mm) | Label Height B Inch (mm) | Labels Per Roll | Rec. Ribbon (M611 / BMP61) |
|---|--------|-------------|-------|----------|-------|--------------------|-------------------------|--------------------------|-----------------|----------------------------|
| B-498 Repositionable Vinyl Cloth | | | | | | | | | | |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-7-498 | B-498 | Vinyl | White | 22 to 16 | 0.500 (12.7) | 0.500 (12.7) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-15-498 | B-498 | Vinyl | White | 22 to 16 | 1.000 (25.4) | 0.275 (7) | 750 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-10-498 | B-498 | Vinyl | White | 16 to 10 | 0.250 (6.35) | 0.750 (19.1) | 750 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-11-498 | B-498 | Vinyl | White | 16 to 10 | 0.500 (12.7) | 0.750 (19.1) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-16-498 | B-498 | Vinyl | White | 12 to 10 | 0.375 (9.53) | 1.000 (25.4) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-17-498 | B-498 | Vinyl | White | 12 to 10 | 1.000 (25.4) | 0.500 (12.7) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-19-498 | B-498 | Vinyl | White | 12 to 10 | 1.000 (25.4) | 1.000 (25.4) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-18-498 | B-498 | Vinyl | White | 10 to 4 | 0.750 (19.05) | 1.000 (25.4) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-30-498 | B-498 | Vinyl | White | 10 to 4 | 0.750 (19.05) | 1.500 (38.1) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-31-498 | B-498 | Vinyl | White | 10 to 4 | 1.500 (38.1) | 1.000 (25.4) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-28-498 | B-498 | Vinyl | White | 10 to 4 | 1.500 (38.1) | 0.250 (6.4) | 750 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-29-498 | B-498 | Vinyl | White | 10 to 4 | 1.500 (38.1) | 0.500 (12.7) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-32-498 | B-498 | Vinyl | White | 10 to 4 | 1.500 (38.1) | 1.500 (38.1) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-21-498 | B-498 | Vinyl | White | - | 1.000 (25.4) | 2.500 (63.5) | 100 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-23-498 | B-498 | Vinyl | White | - | 1.000 (25.4) | 4.000 (101.6) | 100 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-33-498 | B-498 | Vinyl | White | - | 1.500 (38.1) | 4.000 (101.6) | 100 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-34-498 | B-498 | Vinyl | White | - | 1.500 (38.1) | 6.000 (152.4) | 50 | M61-R4310 |
| B-499 Nylon Cloth | | | | | | | | | | |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-7-499 | B-499 | Vinyl | White | 22 to 16 | 0.500 (12.7) | 0.500 (12.7) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-11-499 | B-499 | Vinyl | White | 16 to 10 | 0.500 (12.7) | 0.750 (19.1) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-16-499 | B-499 | Vinyl | White | 12 to 10 | 0.375 (9.53) | 1.000 (25.4) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-19-499 | B-499 | Vinyl | White | 12 to 10 | 1.000 (25.4) | 1.000 (25.4) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-29-499 | B-499 | Vinyl | White | 10 to 4 | 0.500 (12.7) | 1.500 (38.1) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-18-499 | B-499 | Vinyl | White | 10 to 4 | 0.750 (19.05) | 1.000 (25.4) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-30-499 | B-499 | Vinyl | White | 10 to 4 | 0.750 (19.05) | 1.500 (38.1) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-31-499 | B-499 | Vinyl | White | 10 to 4 | 1.000 (25.4) | 1.500 (38.1) | 250 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-28-499 | B-499 | Vinyl | White | 10 to 4 | 1.500 (38.1) | 0.250 (6.4) | 750 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-117-499 | B-499 | Vinyl | White | - | 0.900 (22.86) | 0.500 (12.7) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-84-499 | B-499 | Vinyl | White | - | 0.900 (22.86) | 0.500 (12.7) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-98-499 | B-499 | Vinyl | White | - | 1.000 (25.4) | 0.375 (9.5) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-21-499 | B-499 | Vinyl | White | - | 1.000 (25.4) | 2.500 (63.5) | 100 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-23-499 | B-499 | Vinyl | White | - | 1.000 (25.4) | 4.000 (101.6) | 100 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-81-499 | B-499 | Vinyl | White | - | 1.900 (48.26) | 0.250 (6.4) | 750 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-78-499 | B-499 | Vinyl | White | - | 1.900 (48.26) | 1.000 (25.4) | 250 | M61-R4310 |

High-Temperature Wire and Cable Labels (B-437)

Polyvinylfluoride material for applications where high temperature and self-extinguishing features are required. Heavy-duty performance with excellent resistance to water, oil and other fluids. Meets MIL-M-87958 Standard. Temp. range: -94° F to 275° F (-70° C to 135° C). ROHS compliant.



| Fits Printers | Figure | Catalog # | B# | Material | Color | Label Width A Inch (mm) | Label Height B Inch (mm) | Labels Per Roll | Rec. Ribbon (M611 / BMP61) |
|-----------------------|---------|---------------|-------|-------------------|--------|-------------------------|--------------------------|-----------------|----------------------------|
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-9-437 | B-437 | Polyvinylfluoride | White | 0.650 (16.51) | 0.200 (5.1) | 750 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-10-437 | B-437 | Polyvinylfluoride | White | 0.750 (19.05) | 0.250 (6.4) | 750 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-15-437 | B-437 | Polyvinylfluoride | White | 1.000 (25.4) | 0.275 (7) | 750 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 2 | PTL-29-437 | B-437 | Polyvinylfluoride | White | 1.500 (38.1) | 0.500 (12.7) | 500 | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 33 | PTL-41-437-WT | B-437 | Polyvinylfluoride | White | 1.500 (38.1) | 50 ft. (15.24 m) | 1 roll (cont.) | M61-R4310 |
| M611, BMP61, 71*, TLS | Fig. 33 | PTL-41-437-YL | B-437 | Polyvinylfluoride | Yellow | 1.500 (38.1) | 50 ft. (15.24 m) | 1 roll (cont.) | M61-R4310 |