For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

B0-**IM & B1**IM Speedi Plumb[®] PLUS Braided Icemaker, Humidifier, & Water Filter Connector

Use: For use in potable water distribution systems in accessible locations only.

Design Features:

- Engineered polymer braided fibers bend freely without kinking or crimping
- Reinforced PVC inner hose provides added durability
- Rubber washers provide a large pliable sealing surface and ensure a long lasting water-tight connection

. Ø

Operating Specifications:

Temperature:	40°-160° F, intermittent to 180° F
Pressure:	125 PSI maximum

Tubing Diameter: 0.245" ID (0.470" OD)

CONNECTOR MATERIAL SPECIFICATIONS		
Inner Hose	Reinforced PVC	
Braiding	PVC coated yarn	
Barb	Brass	
Ferrule	Stainless steel	
Washer	Rubber	
Compression Nut	Brass, plated	

Part Listing:

B0-12IM F	1/4" compression x 1/4" compression x 12" length, flag labeled
B0-60IM F	1/4" compression x 1/4" compression x 60" length, flag labeled
B0-60IM P	1/4" compression x $1/4$ " compression x 60" length, bagged
B0-72IM F	1/4" compression x 1/4" compression x 72" length, flag labeled
B0-72IM P	1/4" compression x 1/4" compression x 72" length, bagged
B0-84IM P	1/4" compression x 1/4" compression x 84" length, bagged
B0-96IM P	1/4" compression x 1/4" compression x 96" length, bagged
B0-120IM B	1/4" compression x 1/4" compression x 120" length, bulk
B0-120IM P	1/4" compression x 1/4" compression x 120" length, bagged


This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company, and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.



400.348 B0/B1-**IM SPP Braided IM/Humidifier Connector Comp Inlet REV 07/19 ©2019 Brasscraft Manufacturing Company

BrassCraft

B0-**IM & B1**IM Speedi Plumb[®] PLUS Braided Icemaker, Humidifier, & Water Filter Connector



PART DIMENSIONS (Inches)		
Model	DIM. A	
B0-12IM	12.0 / 13.0	
B0-60IM	60.0/61.0	
B0-72IM	72.0 / 73.0	

PART DIMENSIONS (Inches)			
Model	DIM. A		
B0-84IM	84.0 / 85.0		
B0-96IM	96.0 / 97.0		
B0-120IM	120.0 / 121.0		

Listings & Certifications:

- IAPMO listed to ASME A112.18.6 / CSA B125.6
- IAPMO listed to NSF 372 for Low-Lead Compliance
- IAPMO listed to NSF 61/9

This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company, and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.



400.348 B0/B1-**IM SPP Braided IM/Humidifier Connector Comp Inlet REV 07/19

©2019 Brasscraft Manufacturing Company