# SAFETY DATA SHEET

### 1. Identification

**Product identifier** Rustlick™ EDM-500

Other means of identification

**Part Number** 72055, 72555

Recommended use High performance dielectric oil

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

**Address** 805 E. Old 56 Highway

Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Aspiration hazard Category 1

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word

**Hazard statement** May be fatal if swallowed and enters airways.

**Precautionary statement** 

Prevention Observe good industrial hygiene practices.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Store locked up. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

Hazard(s) not otherwise

classified (HNOC)

None known.

**Supplemental information** None.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Middle		64742-46-7	50 - 60
Distillates (petroleum), Hydrotreated Light		64742-47-8	40 - 50

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Material name: Rustlick™ EDM-500 SDS US 1/6 Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important Aspiration may cause pulmonary edema and pneumonitis.

symptoms/effects, acute and delayed

treatment needed

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. medical attention and special

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

During fire, gases hazardous to health may be formed.

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

General fire hazards Will burn if involved in a fire. No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat and sources of ignition. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

Occupational exposure limits **Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

This mixture has no ingredients that have PEL, TLV, or other recommended exposure limit.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Material name: Rustlick™ EDM-500 SDS US 2/6 Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. Form Liquid.

**Color** Transparent, fluorescent green.

**Odor** Mild

Odor threshold

pH

Not available.

Melting point/freezing point

Initial boiling point and boiling

Not available.

300.2 °F (149 °C)

range

Flash point > 93.0 Pensky-Martens Closed Cup

Evaporation rate < 1

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) Insoluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Explosive properties**Not explosive. **Oxidizing properties**Not oxidizing.

Specific gravity 0.8

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

Conditions to avoid

Carbon oxides.

products

Material name: Rustlick™ EDM-500 sps us

#### 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

Components Species Test Results

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

<u>Acute</u>

**Dermal** 

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7)

**Acute** 

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Oral

LD50 Rat > 5000 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Material name: Rustlick™ EDM-500

Components **Test Results Species** 

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout.donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

No data available. Bioaccumulative potential Not established. Mobility in soil Other adverse effects None known.

#### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

#### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910,1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

categories

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Material name: Rustlick™ EDM-500 SDS US

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### US state regulations

#### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

#### 16. Other information, including date of preparation or last revision

**Issue date** 10-08-2019

Version # 0

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or

expense due to improper use.

Material name: Rustlick™ EDM-500 sps us