PROPERTY.

SAFETY DATA SHEET

1. Identification

Product identifier Rustlick™ 631 (Bulk)

Other means of identification

Part Number 71011, 71051
Recommended use Industrial Use Only
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands **Address** 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAspiration hazardCategory 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from flames and hot surfaces-No smoking. Wear protective gloves/eye protection/face

protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Take off

contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|---------|
| Distillates Petroleum Hydrotreated Light | | 64742-47-8 | 70 - 80 |
| Distillates (petroleum), Hydrotreated Heavy Naphthenic | | 64742-52-5 | 10 - 20 |

Material name: Rustlick™ 631 (Bulk)

Chemical nameCommon name and synonymsCAS number%Calcium Sulfonate26264-06-23.25

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Symptoms may be delayed.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause symptoms/effects, acute and temporary irritation.

delayed

General information

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid. Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

2/7

Material name: Rustlick™ 631 (Bulk) sps us

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| | | OSH. | A |
|---|-------|------|---|
| u | - | USH. | Д |

| Components | Туре | Value | Form | |
|---|------|---------|-----------|--|
| Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) | PEL | 5 mg/m3 | Oil mist. | |

ACGIH

| Components | Туре | Value | Form | |
|---|------|----------|-----------|--|
| Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) | STEL | 10 mg/m3 | Oil mist. | |
| | TWA | 5 mg/m3 | | |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Туре | Value | |
|-------------------------|------|----------|--|
| Vanillin (CAS 121-33-5) | TWA | 10 mg/m3 | |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Face shield is recommended. Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. Hand protection

Wear suitable protective clothing. Other

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Brown.

Hydrocarbon-like. Odor Odor threshold Not available.

8 - 9

Not available. Melting point/freezing point

Initial boiling point and boiling > 249.8 °F (> 121 °C)

range

179.6 °F (82.0 °C) Pensky-Martens Closed Cup Flash point

Evaporation rate < 1

Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Material name: Rustlick™ 631 (Bulk) 71011, 71051 Version #: 01 Issue date: 01-17-2020 Flammability limit - upper

Not available.

Explosive limit - lower (%)

Not available. Explosive limit - upper (%) Not available.

Vapor pressure Not available.

> 1 Vapor density

Relative density Not available.

Solubility(ies)

Insoluble. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature Viscosity** $> 20.5 \text{ mm}^2/\text{s}$

Other information

Explosive properties Not explosive. Oxidizing properties Not oxidizing.

0.82 Specific gravity

VOC 72 % per US State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Skin contact

Eye contact Direct contact with eyes may cause temporary irritation.

May cause discomfort if swallowed. Droplets of the product aspirated into the lungs through Ingestion

ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components **Species Test Results**

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)

Acute **Dermal**

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 2000 mg/kg

Material name: Rustlick™ 631 (Bulk) SDS US Components Species Test Results

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Vapor

LC50 Rat > 0.1 mg/l, 8 Hours

Oral

LD50 Rat > 5000 mg/kg

Vanillin (CAS 121-33-5)

<u>Acute</u>

Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Oral

LD50 Rat 2800 mg/kg

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Vanillin (CAS 121-33-5)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 53 - 61.3 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Material name: Rustlick™ 631 (Bulk)

Partition coefficient n-octanol / water (log Kow)

Vanillin 1.37

Not established. Mobility in soil

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Calcium Sulfonate (CAS 26264-06-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Flammable (gases, aerosols, liquids, or solids) **Classified hazard**

Aspiration hazard categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Material name: Rustlick™ 631 (Bulk) SDS US Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Calcium Sulfonate (CAS 26264-06-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)

Inventory name

International Inventories

Country(s) or region

| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
|-------------|--|-----|
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| | | |

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

01-17-2020 Issue date

Version # 01

United States & Puerto Rico

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

Toxic Substances Control Act (TSCA) Inventory

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or

expense due to improper use.

Product and Company Identification: Alternate Trade Names **Revision information**

Material name: Rustlick™ 631 (Bulk)

SDS US 71011, 71051 Version #: 01 Issue date: 01-17-2020

Yes

On inventory (yes/no)*