

## 1. Identification

<b>Product identifier</b>	<b>LPS® Heavy-Duty Silicone (Aerosol)</b>
<b>Other means of identification</b>	
<b>Part Number</b>	01516, 51516
<b>Recommended use</b>	An industrial lubricant designed to reduce mechanical wear and to extend equipment life of machinery where rubber and plastics are involved and where silicone can be tolerated.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufacturer</b>	
<b>Manufacturer</b>	
<b>Company name</b>	ITW Pro Brands
<b>Address</b>	4647 Hugh Howell Rd. Tucker, GA 30084
<b>Country</b>	(U.S.A.) Tel: +1 770-243-8800
<b>In Case of Emergency</b>	1-800-424-9300 (inside U.S.) +001 703-527-3887 (outside U.S.)
<b>Website</b>	www.lpslabs.com
<b>E-mail</b>	lpssds@itwprobrands.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 2
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Not classified.	
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Warning
<b>Hazard statement</b>	Flammable aerosol. Contains gas under pressure; may explode if heated.
<b>Precautionary statement</b>	
<b>Prevention</b>	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
<b>Response</b>	Wash hands after handling.
<b>Storage</b>	Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of waste and residues in accordance with local authority requirements.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None known.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha, Petroleum, Hydrotreated Heavy		64742-48-9	10 - 20
Petroleum Gases, Liquefied, Sweetened		68476-86-8	14.91
4-chloro-3-methylphenol Sodium Salt		15733-22-9	0.1 - 1
Sodium Benzoate		532-32-1	0.1 - 1
Sorbitan monooleate		1338-43-8	0.1 - 1

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
<b>Most important symptoms/effects, acute and delayed</b>	Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water spray. Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
--	--

**Methods and materials for containment and cleaning up**

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Avoid discharge into drains, water courses or onto the ground.

**Environmental precautions**

**7. Handling and storage**

**Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Level 1 Aerosol.

**Conditions for safe storage, including any incompatibilities**

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage.

**8. Exposure controls/personal protection**

**Occupational exposure limits**

This mixture has no ingredients that have PEL, TLV, or other recommended exposure limit.

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection**

Wear appropriate chemical resistant gloves.

**Other**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

**Appearance**

**Physical state**

Gas.

<b>Form</b>	Aerosol.
<b>Color</b>	White.
<b>Odor</b>	Mild.
<b>Odor threshold</b>	Not established
<b>pH</b>	9.1
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	212 °F (100 °C)
<b>Flash point</b>	142.0 °F (61.1 °C) Tag Closed Cup
<b>Evaporation rate</b>	< 1 BuAc
<b>Flammability (solid, gas)</b>	Flammable gas.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.3 %
<b>Flammability limit - upper (%)</b>	9.5
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	17.5 mm Hg @ 20°C
<b>Vapor density</b>	> 1
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Emulsifies
<b>Partition coefficient (n-octanol/water)</b>	< 1
<b>Auto-ignition temperature</b>	> 572 °F (> 300 °C)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	2000 - 12000 cP @ 25°C
<b>Other information</b>	
<b>Density</b>	7.82
<b>Explosive properties</b>	Not explosive.
<b>Heat of combustion</b>	< 20 kJ/g
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	Not established
<b>Specific gravity</b>	0.92 - 0.94
<b>VOC</b>	CARB 20 % per U.S. State and Federal Consumer Product Regulations.

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.  
**Symptoms related to the physical, chemical and toxicological characteristics** Skin irritation. May cause redness and pain.

**Information on toxicological effects**

**Acute toxicity**

Components	Species	Test Results
Naphtha, Petroleum, Hydrotreated Heavy (CAS 64742-48-9)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 5 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	4800 mg/kg
Sodium Benzoate (CAS 532-32-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<b>Oral</b>		
LD50	Rat	3500 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Not listed.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

**Further information** None known.

**12. Ecological information**

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Poly (Dimethylsiloxane) (CAS 63148-62-9)		
<b>Aquatic</b>		
Fish	LC50 Channel catfish ( <i>Ictalurus punctatus</i> )	2.36 - 4.15 mg/l, 96 hours

Components	Species	Test Results
------------	---------	--------------

Sodium Benzoate (CAS 532-32-1)

**Aquatic**

Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

LPS® Heavy-Duty Silicone (Aerosol) < 1

**Mobility in soil** Not established.

**Other adverse effects** None known.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
D003: Waste Reactive material

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

**14. Transport information**

**DOT**

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not available.  
**Special precautions for user** Not available.  
**Special provisions** N82  
**Packaging exceptions** 306

**IATA**

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not available.  
**Environmental hazards** No.  
**Special precautions for user** Not available.

**IMDG**

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not available.  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** Not available.

**Special precautions for user** Not available.  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**DOT**



**IATA; IMDG**



**General information**

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Toxic Substances Control Act (TSCA)

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

Yes

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations** California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**California Proposition 65**

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Naphtha, Petroleum, Hydrotreated Heavy (CAS 64742-48-9)  
Petroleum Gases, Liquefied, Sweetened (CAS 68476-86-8)

**International Inventories**

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

**Issue date** 10-15-2015

**Revision date** 08-27-2019

**Version #** 04

**Disclaimer** ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision information** Product and Company Identification: Disclosure Overrides  
Physical & Chemical Properties: Multiple Properties