

Provides warranty protection against tampering. Marks will be easily

# STANDARD FEATURES

- Tamper proof torque mark

#### • Performance tested from -40°F to 400°F

### **CROSS CHECK™**

### **TORQUE SEAL®**

### **FEATURES**

- Color options provide traceability
- Boeing Specification: BMS8-45 Type II





Orange, green, red, yellow and blue fluoresce under black/UV light

		Z TUBE
COLOR	PART #	COLOR
ORANGE	83318	BLUE
GREEN	83319	WHITE
RED	83320	PINK
YELLOW	83321	GREY
	ORANGE GREEN RED	ORANGE 83318   GREEN 83319   RED 83320

### **CROSS CHECK™ FAST FAST-DRY TORQUE SEAL®**

### **FEATURES**

- · Dries to the touch: less than a minute
- Full cure time: 24 Hours
- Will not transfer to hands after a minute





Fluoresce under black/UV light

1 0	1 OZ TUBE	
PART #	COLOR	
83514	ORANGE	

## **CROSS CHECK™ PLUS**

### **AVIATION GRADE TORQUE SEAL®**

#### **FEATURES**

- Resistant to Skydrol aviation hydraulic fluid
- · Qualifies to Boeing Specification BMS8-45H, Type I/III
- Approved product replacement for Organic F-925 Torque Seal
- Meets Embraer MEP 09-096 Rev. G
- Dries to the touch: less than a minute
- Full cure time: 24 Hours
- Use on all critical fittings and locknuts during OEM and maintenance procedures
- Perfect for use on landing gear, rotor assemblies, gearboxes, Pal Nuts and more
- · Patent-pending







# **HI-SPOT BLUE**

#### **FEATURES**

- Detects high spots on bearings, gears and other
- Blue, soft, uniform paste spreads easily and evenly
- Never dries out
- Film remains pliable and transferable for months
- Saves time and money in surface scraping work



PART #	CONTAINER SIZE
83307	55 oz Tube