

Clean-Fit Products



BLUE MONSTER Products

Blue Monster Stay-Soft Thread Sealant with PTFE

Specially formulated for residential and commercial fire sprinkler systems

Blue Monster Stay-Soft PTFE enriched pipe thread compound does not harden and allows for pre-fab application to threads weeks before system assembly and pressurization. Stay-Soft is non-seizing and allows for easy disassembly of any threaded connection years after assembly. Easy clean-up and indefinite shelf life.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76023	1/4 pint / 4 fl. oz. / 118 ml	24	18 lbs (8.2 kg)
76025	1/2 pint / 8 fl. oz. / 237 ml	24	26 lbs (11.8 kg)
76027	1 pint / 16 fl. oz. / 473 ml	12	25 lbs (11.3 kg)
76029	1 quart / 32 fl. oz. / .95 liter	12	50 lbs (22.7 kg)

Approved for use on all metal threaded connections, FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings.

Meets Mil. Spec. TT-S-1732
 Temperature range: -15°F (-20°C) to +400°F (204°C)
 Pressure ratings: Gases up to 5,000 PSI (351.5 kg/cm²)
 Liquids up to 10,000 PSI (703.1 kg/cm²)



Blue Monster Industrial Grade Thread Sealant

BLUE MONSTER Industrial Grade Pipe Thread Compound is a slow-drying, soft-setting, non-hardening pipe thread compound. Specially formulated with superb "sticking" characteristics, BLUE MONSTER applies evenly and quickly to threads. Recommended for on-site or assembly line work, BLUE MONSTER is lead-free, non-toxic and will not harden or separate in the can.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76007	2 fl. oz. Squeeze Tube	24	4 lbs.
76009	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76011	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76015	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76019	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

Meets Mil. Spec. TT-S-1732
 Temperature range: -50°F (-45°C) to +400°F (204°C)
 Pressure ratings: Gases up to 3,000 PSI (211 kg/cm²)
 Liquids up to 6,000 PSI (422 kg/cm²)

Not recommended for use on oxygen systems.
 Use Clean-Fit 3-wrap Oxygen PTFE Tape.



Blue Monster Industrial Grade Thread Sealant with PTFE

Formulated for extra lubrication on metal pipe threads, BLUE MONSTER Industrial Grade Thread Sealant with PTFE is a slow-drying, soft-setting, non-hardening pipe thread compound. BLUE MONSTER has a high bulk density, which means there are more solids in the formulation. Recommended for on-site or assembly line work. It is lead-free, non-toxic and will not harden or separate in the can.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76000	2 fl. oz. Squeeze Tube	24	4 lbs.
76001	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76003	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76005	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76017	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

Meets Mil. Spec. TT-S-1732
 Temperature range: -50°F (-45°C) to +400°F (204°C)
 Pressure ratings: Gases up to 3,000 PSI (211 kg/cm²)
 Liquids up to 10,000 PSI (703.1 kg/cm²)

Not recommended for use on oxygen systems.
 Use Clean-Fit 3-wrap Oxygen PTFE Tape.



Blue Monster® Copper Anti-Seize Lubricant

Copper anti-seize lubricant for use on all metal pipe and fittings.

Mill-Rose Blue Monster Copper Anti-Seize is a specially formulated copper-based lubricant for high temperature up to 1800°F (982°C) and high pressure environments. Blue Monster Copper Anti-Seize lubricant will not bleed, separate, or settle. Prevents pressure leakage and seizing resulting from high temperature, freezing, heavy loads, corrosion, and vibration. Contains no grit. Prevents rust and corrosion.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76024	10 oz. / .625 lb. / .283 kg	12	9.4 lbs.
76026	16 oz. / 1.00 lb. / .454 kg	12	15.2 lbs.

- Copper anti-seize lubricant for use on all metal pipe and fittings.
- Temperature Range Use:
 - Gases: -0°F (-17°C) to 1800°F (982°C)
 - Liquids: -0°F (-17°C) to 1800°F (982°C)
 - Brushable to: 10°F (-12°C)
 - Pour Point: 32°F (0°C)