

LOW-VOC SPECIALTY SOLVENT CEMENTS

Dura-Gold™ 627L

● Gold - medium body CPVC solvent cement

Code	Description	Qty.
55992	½ pt.	24
55998	1 pt.	12



PW-G-DWV-WW



FILE NO. 4586

FEATURES

- One-step, no primer needed
- LEED compliant
- 2 year shelf life
- Meets ASTM F493 specs

Application • Chlorinated polyvinyl chloride (CPVC) solvent cement used for joining FlowGuard Gold® CPVC and fittings • All schedules and classes up to 2" schedule 40 and up to 1-¼" on schedule 80

Recommended for

- All CPVC pipe
- Potable water
- Pressure pipe
- DWV systems

*FlowGuard Gold is a licensed trademark of the Lubrizol Corporation



Hot™ 203L

● Blue - medium body PVC solvent cement

Code	Description	Qty.
55988	¼ pt.	24
55989	½ pt.	24
55990	1 pt.	12
55993	1 qt.	12
55994	1 gal.	4



PW-G-DWV-WW



FILE NO. 1796

FEATURES

- Fast drying
- Excellent in cold weather
- LEED compliant
- 2 year shelf life
- Meets ASTM D2564 specs

Application • Polyvinyl chloride (PVC) solvent cement joins both rigid and flexible PVC pipe and socket-type fittings which meet Class 1245 as defined in ASTM specifications D1784 • For all rigid PVC classes up to 6" schedule 40 and 1-¼" schedule 80

Recommended for

- Irrigation • Pools
- Spas • Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems
- Flexible PVC hose



Also available in gal. can

PVC Electrical Conduit 633L

○ Clear/Gray - medium body solvent cement

Code	Description	Qty.
55980	½ pt. - clear	24
55983	1 pt. - clear	12
55985	1 qt. - clear	12
55986	1 gal. - clear	4
55995	1 pt. - gray	12
55996	1 qt. - gray	12



PW-G-DWV-WW



FILE NO. 1796

Clear Only

FEATURES

- Conduit types I & II
- No primer needed on ENT
- LEED compliant
- 2 year shelf life
- Meets ASTM D2564 specs

Application • Clear or gray to match conduit color • Thick formula to reduce runoff • Up to and including 6" Schedule 40 and Schedule 80

Recommended for

- PVC conduit



Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products