

# SYNTHETICS

Minimal upkeep, fast cooling, clear work piece visibility and no mineral oil.

## PowerChip 2000

**Premium synthetic coolant with extreme pressure additives for heavy-duty use.**

### CHARACTERISTICS

- Not susceptible to bacteria or fungus
- Chlorine free
- Good lubricity; minimizes misting
- Recommended for ferrous metals, titanium and high-nickel alloys

### BENEFITS

- Improves coolant life and machine cleanliness
- Excellent quenching and chip removal

| PART NO. | SIZE         |
|----------|--------------|
| 76305    | 5 gal. pail  |
| 76355    | 55 gal. drum |

## SN-100A

**Superior synthetic metalworking coolant used for moderate to heavy-duty machining and sawing operations.**

### CHARACTERISTICS

- Thin dry-film protection; added rust inhibitors
- Rejects tramp oil
- Recommended for ferrous metals and titanium
- Not recommended for aluminum, brass, bronze or copper

### BENEFITS

- Easy to use and maintain; low carry-off
- Protects parts and machines from in-process corrosion

| PART NO. | SIZE         |
|----------|--------------|
| 73058    | 5 gal. pail  |
| 73558    | 55 gal. drum |

## Vytron-N

**Superior synthetic cutting fluid for general-purpose use.**

### CHARACTERISTICS

- No mineral oil or CFCs
- Non-toxic when diluted
- Recommended for ferrous metals and titanium
- Not recommended for aluminum, brass, bronze or copper

### BENEFITS

- Keeps tools and machines clean
- No insoluble soap buildup

| PART NO. | SIZE                |
|----------|---------------------|
| 75014    | 1 gal. jug (4/case) |
| 75054    | 5 gal. pail         |
| 75554    | 55 gal. drum        |

## PowerSaw

**Quality synthetic coolant with performance additives for moderate to heavy-duty use.**

### CHARACTERISTICS

- Specially designed for sawing applications
- Chlorine free
- Recommended for ferrous metals and titanium
- Not recommended for aluminum, brass, bronze or copper

### BENEFITS

- Longer blade life; reduces tooling costs
- Faster cutting times boost productivity

| PART NO. | SIZE         |
|----------|--------------|
| 76205    | 5 gal. pail  |
| 76255    | 55 gal. drum |

