

CATEGORY 2

THREAD SEALANTS, THREAD TAPE

THREAD SEALANTS



TYTE-UNYTE® Non-hardening gray pipe joint compound in paste form. No drip, thixotropic formula. For air, steam, natural gas and water. "Standard of the Industry Since 1900." For use on all metal threads. Meets Federal Specification TT-A-580D. **Made in the U.S.A.**

STOCK CODE	SIZE	CONTAINER	ITEMS/CASE	CASE WEIGHT
T2*	2oz. - .056 kg	Tube**	72	10 lbs. - 4.5 kg
T8	1/2 Pint/1 lb. - .454 kg	Brush Top Can	24	26 lbs. - 11.8 kg
T8C*	1/2 Pint/1 lb. - .454 kg	Brush Top Can	24	26 lbs. - 11.8 kg
T16	Pint/2 lbs. - .92 kg	Brush Top Can	12	25 lbs. - 11.3 kg
T6	6 lbs. - 2.72 kg	Pail w/ Handle	4	31 lbs. - 14.1 kg
T50	50 lbs./5 gal. - 22.68 kg	Pail w/ Handle	1	54 lbs. - 24.5 kg
T600	600 lbs./55 gal. - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg



STEEL-UNYTE Pipe joint, thread and hard set sealer, dark gray, semi-paste for use on all metal threaded connections and flanges. Meets Military Specification MIL-S-7916B. Meets International Fuel Gas Code 403.9.3 for Thread Joint Compounds. **Made in the U.S.A.**

ST4	1/4 Pint - 118 ml	Brush Top Can	24	14 lbs. - 6.4 kg
ST8	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg
ST8A	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	11 lbs. - 5.0 kg
ST16	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg
ST5	5 Gallon - 18.9 L	Pail w/ Handle	1	65 lbs. - 29.5 kg
ST55	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg



T-U TYPE 555 Soft-set, yellow thread sealing compound for use on plastic and metal threaded systems carrying air, steam, petroleum, water, gases and many chemicals. Meets Federal Specification TT-S-1732. Meets International Fuel Gas Code 403.9.3 for Thread Joint Compounds. **Made in the U.S.A.**

TU4	1/4 Pint - 118 ml	Brush Top Can	24	14 lbs. - 6.4 kg
TU8	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg
TU8C*	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg
TU16	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg
TU32	Quart - .95 L	Brush Top Can	12	41 lbs. - 18.6 kg
TU5	5 Gallon - 18.9 L	Pail w/ Handle	1	65 lbs. - 29.5 kg
TU55	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg



BLUE MAGIC All purpose, non-seizing, industrial grade pipe thread compound that produces a leakproof seal on all types of metal and plastic threaded connections. Suitable for ABS, PVC, and CPVC threaded connections. Approved for use on Spears FlameGuard® CPVC Systems. Meets Federal Specification TT-S-1732. Meets International Fuel Gas Code 403.9.3 for Thread Joint Compounds. **Made in the U.S.A.**

IG2	2 oz. - .056 kg	Tube**	72	11 lbs. - 5.0 kg
IG4	1/4 Pint - 118 ml	Brush Top Can	24	15 lbs. - 6.8 kg
IG8	1/2 Pint - 237 ml	Brush Top Can	24	24 lbs. - 10.9 kg
IG8A	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg
IG8C*	1/2 Pint - 237 ml	Brush Top Can	24	24 lbs. - 10.9 kg
IG8CA*	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg
IG16	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg
IG16C*	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg
IG32	Quart - .95 L	Brush Top Can	12	42 lbs. - 19.1 kg
IG5	5 Gallon - 18.9 L	Pail w/ Handle	1	65 lbs. - 29.5 kg
IG55	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg



pw-G/dwv/sw



Compatible



SELECT-UNYTE Soft-set, white all purpose PTFE paste thread sealing compound. For use on plastic and metal threaded systems carrying air, steam, petroleum, water, gases and many chemicals. Meets Federal Specification TT-S-1732. Meets International Fuel Gas Code 403.9.3 for Thread Joint Compounds. **Made in the U.S.A.**

TF2	2 oz. - .056 kg	Tube**	72	11 lbs. - 5.0 kg
TF4	1/4 Pint - 118 ml	Brush Top Can	24	15 lbs. - 6.8 kg
TF8	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg
TF8A	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg
TF8C*	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg
TF8CA*	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg
TF16	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg
TF16C*	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg
TF32	Quart - .95 L	Brush Top Can	12	43 lbs. - 19.5 kg
TF32C*	Quart - .95 L	Brush Top Can	12	43 lbs. - 19.5 kg
TF5	5 Gallon - 18.9 L	Pail w/ Handle	1	66 lbs. - 29.9 kg
TF55	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg

*Bilingual Label: French and English. **Tubes Packed 12 Per Clear Plastic Tub. FlameGuard® is a registered trademark of Spears Manufacturing Company. Pallet Quantities for Thread Sealants: 1/4 Pint = 130 Cases, 1/2 Pint = 80 Cases, 1 Pint = 80 Cases, 1 Quart = 56 Cases, 1 Gallon = 45 Cases