

LOCKING TOOLS

LOCKING WRENCHES/C-CLAMPS

WISE-GRIP® Locking Wrenches with Wire Cutter



04

- Jaw locks onto three sides of a hex fastener and won't slip or mar

WISE-GRIP Locking C-Clamps with Regular Tips



19



19T

- Wide-opening jaw provides greater versatility in clamping a variety of shapes

WISE-GRIP Locking C-Clamps with Swivel Pads



20

- Swivel pads hold tapered work, awkward fabricating jobs and delicate projects without damaging the work surface

Original Handle

Description	Size	Jaw Adjustment	Carded Stock #
10LW®	10" (250 mm)	5/8" - 1-1/8" (16 mm - 28 mm)	02
7LW®	7" (175 mm)	7/16" - 3/4" (11 mm - 19 mm)	04
4LW®	4" (100 mm)	1/4" - 9/16" (7 mm - 14 mm)	08

Original Handle

Description	Size	Jaw Adjustment	Throat Depth	Stock #
24R™	24" (605 mm)	0" - 10" (0 mm - 254 mm)	15 - 1/2" (394 mm)	275
18DR™	18" (455 mm)	0" - 7-1/2" (0 mm - 190 mm)	9 - 1/2" (241 mm)	211
18R®	18" (455 mm)	0" - 8" (0 mm - 200 mm)	9 - 1/2" (241 mm)	21
11R®	11" (275 mm)	0" - 3-3/8" (0 mm - 85 mm)	2 - 5/8" (67 mm)	19
9DR™	9" (225 mm)	0" - 4-1/2" (0 mm - 112 mm)	4 - 3/4" (121 mm)	30
6R®	6" (150 mm)	0" - 2" (0 mm - 50 mm)	1 - 1/2" (38 mm)	17

Fast Release™ Handle

Description	Size	Jaw Adjustment	Carded Stock #
11R®	11" (275 mm)	0" - 3-3/8" (0 mm - 85 mm)	19T
6R®	6" (150 mm)	0" - 2" (0 mm - 50 mm)	17T

Original Handle

Description	Size	Jaw Adjustment	Throat Depth	Stock #
24SP™	24" (605 mm)	0" - 10" (0 mm - 254 mm)	15 - 1/2" (394 mm)	28
18SP™	18" (455 mm)	0" - 8" (0 mm - 200 mm)	9 - 1/2" (241 mm)	22
11SP®	11" (275 mm)	0" - 3-3/8" (0 mm - 85 mm)	2 - 5/8" (67 mm)	20
9SP™	9" (225 mm)	0" - 4-1/2" (0 mm - 112 mm)	4 - 3/4" (121 mm)	31
6SP™	6" (150 mm)	0" - 2" (0 mm - 50 mm)	1 - 1/2" (38 mm)	18
4SP™	4" (100 mm)	0" - 1-5/8" (0 mm - 41 mm)	1 - 1/4" (32 mm)	165