


Negative rhombic 80°

CNMG / CNGG / CNMA / CNMM

Tiger-tec® Silver



Indexable inserts

Designation	r mm	f mm	ap mm	P				M				K				S					
				HC	WPP01	WPP05S	WPP10S	WPP20S	WPP30S	WMP20S	WMP20S	WSM10	WSM20	WSM30	WKK10S	WKK20S	WKK30S	WAK30	WSM10	WSM20	WSM30
	CNMG120408-NR4	0,8	0,22–0,40	1,2–5,0						☺	☺	☺	☺	☺				☺	☺	☺	☺
	CNMG120412-NR4	1,2	0,25–0,50	1,5–5,0						☺	☺	☺	☺	☺				☺	☺	☺	☺
	CNMG120416-NR4	1,6	0,30–0,55	2,0–5,0														☺	☺	☺	☺
	CNMG160608-NR4	0,8	0,22–0,45	1,2–7,0														☺	☺	☺	☺
	CNMG160612-NR4	1,2	0,25–0,60	1,5–7,0						☺	☺	☺	☺	☺				☺	☺	☺	☺
	CNMG160616-NR4	1,6	0,30–0,65	2,0–7,0														☺	☺	☺	☺
	CNMG190612-NR4	1,2	0,25–0,60	1,5–8,0						☺	☺	☺	☺	☺				☺	☺	☺	☺
	CNMG190616-NR4	1,6	0,30–0,80	2,0–8,0						☺	☺	☺	☺	☺				☺	☺	☺	☺
	CNMG120408-RP5	0,8	0,20–0,40	0,8–6,0		☺	☺	☺	☺								☺	☺			
	CNMG120412-RP5	1,2	0,25–0,60	1,0–6,0		☺	☺	☺	☺								☺	☺			
	CNMG120416-RP5	1,6	0,35–0,70	1,6–6,0		☺	☺	☺	☺												
	CNMG160608-RP5	0,8	0,20–0,45	1,0–8,0		☺	☺	☺	☺												
	CNMG160612-RP5	1,2	0,25–0,60	1,2–8,0		☺	☺	☺	☺								☺				
	CNMG160616-RP5	1,6	0,35–0,70	1,6–8,0		☺	☺	☺	☺								☺				
	CNMG160624-RP5	2,4	0,40–0,90	2,0–8,0		☺	☺	☺	☺												
	CNMG190608-RP5	0,8	0,20–0,50	1,0–10,0		☺	☺	☺	☺												
	CNMG190612-RP5	1,2	0,25–0,65	1,2–10,0		☺	☺	☺	☺												
	CNMG190616-RP5	1,6	0,35–0,80	1,6–10,0		☺	☺	☺	☺												
	CNMG190624-RP5	2,4	0,45–1,00	2,0–10,0		☺	☺	☺	☺												
	CNMG250924-RP5	2,4	0,45–1,20	2,0–12,0		☺	☺	☺	☺												
	CNMG120408-RP7	0,8	0,25–0,50	0,8–5,0		☺	☺	☺	☺								☺				
	CNMG120412-RP7	1,2	0,30–0,50	1,2–5,0		☺	☺	☺	☺								☺				
	CNMG120416-RP7	1,6	0,35–0,50	1,5–5,0		☺	☺	☺	☺												
	CNMG160608-RP7	0,8	0,30–0,50	0,8–6,0		☺	☺	☺	☺												
	CNMG160612-RP7	1,2	0,35–0,60	1,2–6,0		☺	☺	☺	☺								☺				
	CNMG160616-RP7	1,6	0,40–0,60	1,5–6,0		☺	☺	☺	☺								☺				
	CNMG190612-RP7	1,2	0,35–0,60	1,2–7,0		☺	☺	☺	☺								☺				
	CNMG190616-RP7	1,6	0,40–0,60	1,5–7,0		☺	☺	☺	☺									☺			
	CNMG250924-RP7	2,4	0,45–1,00	3,0–9,0		☺											☺				
	CNMA120404-RK5	0,4	0,16–0,25	0,6–5,0													☺	☺			
	CNMA120408-RK5	0,8	0,25–0,50	0,8–5,0													☺	☺			
	CNMA120412-RK5	1,2	0,30–0,50	1,2–5,0													☺	☺			
	CNMA120416-RK5	1,6	0,35–0,70	1,5–5,0													☺	☺			
	CNMA160612-RK5	1,2	0,35–0,70	1,2–7,0													☺	☺			
	CNMA160616-RK5	1,6	0,35–0,80	1,5–7,0													☺	☺			
	CNMA190612-RK5	1,2	0,30–0,65	1,2–8,0													☺	☺			
	CNMA190616-RK5	1,6	0,35–0,80	1,5–8,0													☺	☺			
	CNMA190624-RK5	2,4	0,40–0,90	2,5–8,0													☺	☺			

See the ISO 1832 designation key for dimensions

HC = Coated carbide

HW = Uncoated carbide



A 234



A 244



A 256



A 80



A 190