

RAPID SL FOR SEAGRAM® WALL-HUNG TOILET



D29054026.000 – 2x6 Carrier with Welded Brackets



• **GROHE Whisper®** = Innovative water technology delivering whisper-quiet acoustics



• **GROHE EcoJoy™** = Save precious resources and enjoy 100% water comfort



• **GROHE ToolFree** = no tools are needed to connect the main water supply, flexible hose and inspection shaft



• **GROHE EasyConnect** = A pneumatic hose connects the flush valve to the flush plate to accommodate all tile thicknesses



• **GROHE QuickFix™** = concept ensures flexibility and ease of installation, cutting installation time significantly



• **GROHE VarioPort** = the supply hose can be attached at four points: front, rear, left or right



• **GROHE Safety, Rapid SL** certifies load bearing capacity and stability of the carrier has been confirmed at 880 lbs. (400 kg)

- For on-the-wall or studded wall installations
- Water supply from left, right or back
- Flushing cistern 1.6 gal and .8 gal
- Pneumatic discharge valve offering 3 modes of operation: dual flush, start/stop or single flush for vertical or horizontal use
- Integrated vertical support brackets w/ 7" - 9" mounting screw distance
- Powder coated self-supporting steel frame w/ quick and lockable adjustments
- 44" installation height

CODES AND STANDARDS

Meets or Exceeds EPA92 / ASME A112.6.2 / CSA B125.3

AVAILABLE FINISHES

Polished Chrome	100
Brushed Nickel	144
Platinum Nickel	150

FINISH CODE

DESCRIPTION

Skate Cosmopolitan DF Actuator	D28015000.144
Skate Cosmopolitan DF Actuator	D28015000.150
Skate Cosmopolitan DF Actuator	D28015000.100

PRODUCT NUMBER

ROUGH-IN DIAGRAM
SHOWN ON NEXT PAGE

RAPID SL FOR SEAGRAM® WALL-HUNG TOILET

