

Legris Metric Push-In Fittings

Male Branch Tees

| Tube OD | Male BSPT | Nylon / Nickel Plated Brass Part # | Pkg Qty |
|---------|-----------|------------------------------------|---------|
| 4 mm | 1/8" | 31080410 | 10 |
| 4 mm | 1/4" | 31080413 | 10 |
| 6 mm | 1/8" | 31080610 | 10 |
| 6 mm | 1/4" | 31080613 | 10 |
| 8 mm | 1/8" | 31080810 | 10 |
| 8 mm | 1/4" | 31080813 | 10 |



- body is orientable for positioning purposes

Nylon Tubing

Features:

- translucent color
- resistant to fungus, abrasion, moisture and UV
- temperature range: **-60°F to 200°F (-51°C to 93°C)**

| Size | | Wall Thickness | Working Pressure @ 75°F (24°C) | Length | Part # |
|------|--------|----------------|--------------------------------|--------|------------------|
| OD | ID | | | | |
| 4 mm | 2.7 mm | .65 mm | 350 | 25 m | 1025P0400 |
| 6 mm | 4 mm | 1 mm | 340 | 25 m | 1025P0600 |
| 8 mm | 6 mm | 1 mm | 250 | 25 m | 1025P0800 |



Tubing cutters sold on page 892

Male Threaded Connectors

Feature:

- internal hex allows ease of assembly in tight places

| Tube OD | Male Thread | Nickel Plated Brass Part # | Pkg Qty |
|---------|-------------|----------------------------|---------|
| 4 mm | M5 | 31010419 | 10 |
| 4 mm | 1/8 BSPP | 31010410 | 10 |
| 6 mm | M5 | 31010619 | 10 |
| 6 mm | 1/8 BSPP | 31010610 | 10 |
| 6 mm | 1/4 BSPP | 31010613 | 10 |
| 8 mm | 1/8 BSPP | 31010810 | 10 |
| 8 mm | 1/4 BSPP | 31010813 | 10 |
| 10 mm | 1/4 BSPP | 31011013 | 10 |



Bulkhead Union

| Tube OD | Tube OD | Nylon Part # | Pkg Qty |
|---------|---------|-----------------|---------|
| 6 mm | 6 mm | 31160600 | 10 |



Unions

| Tube OD | Tube OD | Nylon Part # | Pkg Qty |
|---------|---------|-----------------|---------|
| 4 mm | 6 mm | 31060406 | 10 |
| 6 mm | 6 mm | 31060600 | 10 |
| 10 mm | 10 mm | 31061000 | 10 |

