


Flat Hex Manifolds

Feature:

- designed to lay flat on the floor, safely distributing three hose lines to the work area

| NPT Inlet (1) | NPT Outlets (3) | Brass Part # |
|---------------|-----------------|-----------------|
| 1/4" | 1/4" | 3122 |
| 3/8" | 1/4" | 3132 |
| 3/8" | 3/8" | 3133 |



Compressor Y

Feature:

- converts a single supply source to a dual outlet

| Female NPT Inlet (1) | Male NPT Outlets (2) | Iron Part # |
|----------------------|----------------------|----------------|
| 1" | 3/4" | Y10075 |



Anti-Freeze Lubricants

Application:

- winter grade air tool lubricant prevents air line, air tool and in-line lubricator freeze-up

Features:

- can be poured directly into tool or used with air line lubricators
- minimum temperature **-45°F (-43°C)**

| Size | Part # | Optional Qty |
|----------|-----------------|--------------|
| 1 pint | DATL016W | 12 |
| 1 gallon | DATL128W | 4 |



pint



gallon

Air Tool Lubricants

Application:

- high grade lubricant prolongs the service life of air tools, cylinders and accessories

Features:

- #10 weight lubricant
- compound is superior in performance to ordinary lubricants
- prohibits rust and removes moisture as it lubricates
- non-corrosive, non-reactive and does not decompose
- easy pour spout helps prevent costly spills
- use with the in-line lubricators on page 368

| Size | Part # | Optional Qty |
|----------|----------------|--------------|
| 1 pint | DATL016 | 12 |
| 1 gallon | DATL128 | 4 |



pint



gallon