

## Boss™ Ground Joint Male Spuds


| Thread | Plated Steel<br>Part # | Plated Iron<br>Part # |
|--------|------------------------|-----------------------|
| 3/8"   | <b>GMC<sup>1</sup></b> | ---                   |
| 1/2"   | <b>GM3</b>             | ---                   |
| 3/4"   | <b>GM8</b>             | ---                   |
| 1"     | <b>GM13</b>            | ---                   |
| 1 1/4" | ---                    | <b>GM18</b>           |
| 1 1/2" | ---                    | <b>GM23</b>           |
| 2"     | ---                    | <b>GM28</b>           |
| 2 1/2" | ---                    | <b>GM33</b>           |
| 3"     | ---                    | <b>GM38</b>           |

Hose Coupling  
Systems

<sup>1</sup> 1/4", 3/8" and 6" available only with copper seat spuds, all other sizes have polymer seats


## Boss™ Ground Joint Double Spuds

| Thread            | Plated Steel<br>Part # | Plated Iron<br>Part # |
|-------------------|------------------------|-----------------------|
| 1/2"              | <b>GDB3</b>            | ---                   |
| 3/4" and 1"       | <b>GDB13</b>           | ---                   |
| 1 1/4" and 1 1/2" | ---                    | <b>GDB23</b>          |
| 2"                | ---                    | <b>GDB28</b>          |
| 2 1/2"            | ---                    | <b>GDB33</b>          |
| 3"                | ---                    | <b>GDB38</b>          |



## Boss Holedall™ Fittings


## Applications:

- designed for air and liquid applications where a permanent, low profile clamping system is desired
- not for steam service 

## Features:

- supplied with carbon steel ferrules
- consult Dixon® for swage and/or crimp specifications

| Size   | Hose OD  |          | Plated Iron / Steel<br>Part # | Stainless Steel<br>Part # |
|--------|----------|----------|-------------------------------|---------------------------|
|        | From     | To       |                               |                           |
| 3/4"   | 1-10/64" | 1-14/64" | <b>GF26P1</b>                 | ---                       |
|        | 1-15/64" | 1-18/64" | <b>GF26P2</b>                 | ---                       |
|        | 1-19/64" | 1-22/64" | <b>GF26P3</b>                 | ---                       |
| 1"     | 1-30/64" | 1-34/64" | <b>GF36P1</b>                 | ---                       |
|        | 1-35/64" | 1-38/64" | <b>GF36P2</b>                 | ---                       |
|        | 1-39/64" | 1-42/64" | <b>GF36P3</b>                 | ---                       |
| 1 1/2" | 1-58/64" | 2"       | <b>GF61P1</b>                 | <b>RGF61P1</b>            |
|        | 2-1/64"  | 2-8/64"  | <b>GF61P2</b>                 | <b>RGF61P2</b>            |
|        | 2-9/64"  | 2-16/64" | <b>GF61P3</b>                 | ---                       |
| 2"     | 2-28/64" | 2-40/64" | <b>GF81P1</b> <sup>1</sup>    | <b>RGF81P1</b>            |
|        | 2-41/64" | 2-48/64" | <b>GF81P2</b> <sup>1</sup>    | <b>RGF81P2</b>            |
|        | 2-49/64" | 2-56/64" | <b>GF81P3</b> <sup>1</sup>    | ---                       |
| 3"     | 3-30/64" | 3-40/64" | <b>GF111P1</b> <sup>1</sup>   | ---                       |
|        | 3-41/64" | 3-48/64" | <b>GF111P2</b> <sup>1</sup>   | ---                       |
|        | 3-49/64" | 3-56/64" | <b>GF111P3</b> <sup>1</sup>   | ---                       |



<sup>1</sup> 2" and 3" have a machined shank