

### Ball Shut-Offs



**Features:**

- full time swivel base ensures durable rubber-like handle can be positioned for easy operation
- maximum operating pressure: **100 PSI** (water only) at **70°F (21°C)**

Thread	Length	Waterway	Cast Brass Part #
1½" NST (NH)	4¾"	1⅜"	<b>BSO150NST</b>
1½" NPSH	4¾"	1⅜"	<b>BSO150S</b>

#### Replacement Part



Description	Composite Part #
replacement handle	<b>BSO150-H</b>

### Nozzle Tips



**Features:**

- straight stream only
- maximum operating pressure: **100 PSI** (water only) at **70°F (21°C)**
- **74 GPM @ 100 PSI**

Thread	Length	Orifice	Satin Brass Part #
1" NST (NH)	4¾"	½"	<b>BNT100F</b>
1" NPSH	4¾"	½"	<b>BNT100S</b>
1½" NST (NH)	4⅜"	½"	<b>BNT150F</b>
1½" NPSH	4⅜"	½"	<b>BNT150S</b>

### Plain Hose Nozzles



**Features:**

- finish: satin
- maximum operating pressure: **100 PSI** (water only) at **70°F (21°C)**

Size	Thread	Overall Length	Orifice	Replacement Gasket	Previous Part #	Brass
						Part #
¾"	GHT	6"	1/4"	<b>KRW5</b>	500SN6	<b>BN6</b>
¾"	NPSH	6"	1/4"	<b>KRW5</b>	---	<b>BN7</b>
1"	NPSH	8"	5/16"	<b>KRW10</b>	---	<b>BN10</b>
1¼"	NPSH	10"	3/8"	<b>KRW15</b>	---	<b>BN12</b>
1½"	NPSH	10"	1/2"	<b>KRW20</b>	---	<b>BN15</b>
2"	NPSH	12"	9/16"	<b>SW200</b>	---	<b>BN20</b>
2½"	NPSH	12"	1"	<b>KRW35</b>	---	<b>BN25</b>
1"	NST (NH)	8"	5/16"	<b>SW100F</b>	---	<b>BN10F</b>
1½"	NST (NH)	10"	1/2"	<b>SW150</b>	---	<b>BN15F</b>
2½"	NST (NH)	12"	1"	<b>SW250</b>	---	<b>BN25F</b>
1½"	NYFD	10"	1/2"	<b>SW150</b>	---	<b>BN15NYFD</b>
2½"	NYFD	12"	1"	<b>SW250</b>	---	<b>BN25NYFD</b>

### Twist Nozzles



**Feature:**

- maximum operating pressure **150 PSI** (water only)

Thread Size	Length	Previous Part #	Extruded Brass Part #
¾" GHT	4"	---	<b>BTN75</b>
	4"	---	<b>500AN4<sup>1</sup></b>
	6¾"	500-AN7	<b>500AN7<sup>1</sup></b>

<sup>1</sup> imported