

PVC Braided Tubing

Application:

- for use with standard shank fittings in low pressure liquid and pneumatic applications

domestic

Features:

- high grade tensile strength polyester yarn reinforcement
- temperature range: **27°F to 150°F (-3°C to 66°C)**
- shipped in coils, *sold only in lengths shown below*

| Size | | Working Pressure PSI @ 72°F (22°C) | Length | Clear PVC Part # |
|-------|--------|---------------------------------------|--------|---------------------|
| OD | ID | | | |
| .394 | 3/16" | 315 | 300' | BR0306 |
| .435 | 1/4" | 315 | 300' | BR0446 |
| .625 | 3/8" | 265 | 300' | BR0609 |
| .728 | 1/2" | 215 | 300' | BR0812 |
| .906 | 5/8" | 200 | 300' | BR1014 |
| 1.024 | 3/4" | 150 | 300' | BR1218 |
| 1.732 | 1-1/4" | 110 | 100' | BR2027 |
| 1.950 | 1-1/2" | 90 | 100' | BR2431 |



imported

Features:

- for various machine tools and the transportation of chemicals
- temperature range: **14°F to 149°F (-10°C to 65°C)**
- shipped in bundles wrapped with PVC film, *sold only in lengths shown below*

| Size | | Working Pressure PSI @ 72°F (22°C) | Length | Clear PVC Part # |
|---------|------|---------------------------------------|--------|---------------------|
| OD | ID | | | |
| 1/2" | 1/4" | 142 | 300' | IBR0446 |
| 5/8" | 3/8" | 114 | 300' | IBR0609 |
| 3/4" | 1/2" | 100 | 300' | IBR0812 |
| 1-1/16" | 3/4" | 71 | 300' | IBR1218 |
| 1-5/16" | 1" | 71 | 200' | IBR1621 |



D.O.T. Air Brake Tubing Rolls

Features:

- meets Department of Transportation FMVSS-106 nylon material conforming to SAE J844
- working pressure: **150 PSI**
- temperature range: **-40°F to 200°F (-40°C to 93°C)**
- tubing cutters sold on page 892

| Tube Size | Tubing Color | Length | Nylon Part # |
|-----------|--------------|--------|-----------------------|
| 3/16" | black | 100' | J844-03-BL-100 |
| 1/4" | black | 100' | J844-04-BL-100 |
| | blue | 100' | J844-04-B-100 |
| | red | 100' | J844-04-R-100 |
| 3/8" | black | 100' | J844-06-BL-100 |
| | blue | 100' | J844-06-B-100 |
| | red | 100' | J844-06-R-100 |
| 1/2" | black | 100' | J844-08-BL-100 |
| 5/8" | black | 100' | J844-10-BL-100 |
| 3/4" | black | 100' | J844-12-BL-100 |

