



Design features:

- Constructed using high grade, engineered aluminum
- Tempered clear safety glass
- Available in Bright Silver, Brushed Nickel or Black Bronze finishes
- Doors include rollers with long life bearings for years of smooth, maintenance-free operation
- Adjustable for out-of-plumb walls
- Integral pull handle
- Easy to install and clean
- Frameless or framed designs available
- Frameless glass is 3/16" thick

Code Accepted

STYLEMATE® Enclosures meet or exceed performance requirements as listed:


- American National Standards Institute (ANSI) Specification Z 97.1



Specifications


Model	Finish	Glass	H	Opening	UPC	Fits DURABASE®
Framed Design						
48.403	Bright Silver	Clear	69"	47"	6 71031 00466 6	3448M, 3248M
Frameless Design						
48.406	Bright Silver	Clear	69"	47"	6 71031 00469 7	3448M, 3248M
48.407	Brushed Nickel	Clear	69"	47"	6 71031 00470 3	3448M, 3248M
48.408	Black Bronze	Clear	69"	47"	6 71031 00471 0	3448M, 3248M
Framed Design						
60.403	Bright Silver	Clear	69"	59"	6 71031 00472 7	3260M, 3460M, 3060 (L/R)
Frameless Design						
60.406	Bright Silver	Clear	69"	59"	6 71031 00475 8	3260M, 3460M, 3060 (L/R)
60.407	Brushed Nickel	Clear	69"	59"	6 71031 00476 5	3260M, 3460M, 3060 (L/R)
60.408	Black Bronze	Clear	69"	59"	6 71031 00477 2	3260M, 3460M, 3060 (L/R)

Framed Design:



General: Furnish and install as shown on plans, a STYLEMATE® By-Pass enclosure as manufactured by E.L. Mustee & Sons, Inc. Model _____ with a bright (Bright Silver, Brushed Nickel, Black Bronze) finish. Shall be by-pass style with aluminum frame and clear tempered safety glass panel. Continuous pull handle. Out-of-plumb condition up to 1" can be adjusted. Shall meet ANSI Specifications Z97.1.

Frameless Design:



General: Furnish and install as shown on plans, a STYLEMATE® Frameless By-Pass enclosure as manufactured by E.L. Mustee & Sons, Inc. Model _____ with a bright (Bright Silver, Brushed Nickel, Black Bronze) finish. Shall be a frameless style by-pass door with aluminum top and bottom track and clear tempered safety glass panels. Continuous pull handle. Out-of-plumb condition up to 1" can be adjusted. Shall meet ANSI Specifications Z97.1.

