


Count	Description																																												
1	<p data-bbox="225 338 371 367"><b>UP 26-96 SF</b></p> <div data-bbox="248 414 579 669">  </div> <p data-bbox="619 680 1070 707" style="text-align: center;">Product photo could vary from the actual product</p> <p data-bbox="225 712 491 741">Product No.: <a href="#">98961756</a></p> <p data-bbox="225 743 746 831">The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing.</p> <p data-bbox="225 833 770 862">The bearings are lubricated by the pumped liquid.</p> <p data-bbox="225 864 560 893">The pump is characterized by:</p> <ul data-bbox="264 896 807 1039" style="list-style-type: none"> <li>* Ceramic shaft and radial bearings.</li> <li>* Carbon axial bearing.</li> <li>* Stainless steel rotor can and bearing plate.</li> <li>* Corrosion-resistant impeller, Composite, PES.</li> <li>* Stainless steel pump housing.</li> </ul> <p data-bbox="225 1070 560 1099">The motor is a 1-phase motor.</p> <p data-bbox="225 1102 687 1131">No additional motor protection is required.</p> <p data-bbox="225 1162 312 1191"><b>Liquid:</b></p> <table data-bbox="225 1193 722 1308"> <tr> <td>Pumped liquid:</td> <td>Water</td> </tr> <tr> <td>Liquid temperature range:</td> <td>2 .. 110 °C</td> </tr> <tr> <td>Selected liquid temperature:</td> <td>60 °C</td> </tr> <tr> <td>Density:</td> <td>983.2 kg/m<sup>3</sup></td> </tr> </table> <p data-bbox="225 1339 352 1368"><b>Technical:</b></p> <table data-bbox="225 1370 687 1400"> <tr> <td>Approvals on nameplate:</td> <td>UL, CSA</td> </tr> </table> <p data-bbox="225 1431 344 1460"><b>Materials:</b></p> <table data-bbox="225 1462 772 1547"> <tr> <td>Pump housing:</td> <td>Stainless steel EN 1.4301</td> </tr> <tr> <td>Impeller:</td> <td>Composite, PES</td> </tr> </table> <p data-bbox="225 1579 368 1608"><b>Installation:</b></p> <table data-bbox="225 1610 751 1843"> <tr> <td>Maximum ambient temperature:</td> <td>40 °C</td> </tr> <tr> <td>Ambient max at 176°F liquid:</td> <td>80 °C</td> </tr> <tr> <td>Maximum operating pressure:</td> <td>10 bar</td> </tr> <tr> <td>Flange standard:</td> <td>USA Oval</td> </tr> <tr> <td>Type of connection:</td> <td>S.S. Flange</td> </tr> <tr> <td>Pipe connection:</td> <td>2 - Bolt Flange</td> </tr> <tr> <td>Pressure stage:</td> <td>10</td> </tr> <tr> <td>Port-to-port length:</td> <td>165 mm</td> </tr> </table> <p data-bbox="225 1874 405 1904"><b>Electrical data:</b></p> <table data-bbox="225 1906 727 2107"> <tr> <td>Max. power input:</td> <td>205 W</td> </tr> <tr> <td>Main frequency:</td> <td>60 Hz</td> </tr> <tr> <td>Rated voltage:</td> <td>1 x 115 V</td> </tr> <tr> <td>Current in speed 3:</td> <td>1.7 A</td> </tr> <tr> <td>Capacitor size - run:</td> <td>10 µF/180 V</td> </tr> <tr> <td>Number of poles:</td> <td>2</td> </tr> <tr> <td>Insulation class (IEC 85):</td> <td>F</td> </tr> </table>	Pumped liquid:	Water	Liquid temperature range:	2 .. 110 °C	Selected liquid temperature:	60 °C	Density:	983.2 kg/m <sup>3</sup>	Approvals on nameplate:	UL, CSA	Pump housing:	Stainless steel EN 1.4301	Impeller:	Composite, PES	Maximum ambient temperature:	40 °C	Ambient max at 176°F liquid:	80 °C	Maximum operating pressure:	10 bar	Flange standard:	USA Oval	Type of connection:	S.S. Flange	Pipe connection:	2 - Bolt Flange	Pressure stage:	10	Port-to-port length:	165 mm	Max. power input:	205 W	Main frequency:	60 Hz	Rated voltage:	1 x 115 V	Current in speed 3:	1.7 A	Capacitor size - run:	10 µF/180 V	Number of poles:	2	Insulation class (IEC 85):	F
Pumped liquid:	Water																																												
Liquid temperature range:	2 .. 110 °C																																												
Selected liquid temperature:	60 °C																																												
Density:	983.2 kg/m <sup>3</sup>																																												
Approvals on nameplate:	UL, CSA																																												
Pump housing:	Stainless steel EN 1.4301																																												
Impeller:	Composite, PES																																												
Maximum ambient temperature:	40 °C																																												
Ambient max at 176°F liquid:	80 °C																																												
Maximum operating pressure:	10 bar																																												
Flange standard:	USA Oval																																												
Type of connection:	S.S. Flange																																												
Pipe connection:	2 - Bolt Flange																																												
Pressure stage:	10																																												
Port-to-port length:	165 mm																																												
Max. power input:	205 W																																												
Main frequency:	60 Hz																																												
Rated voltage:	1 x 115 V																																												
Current in speed 3:	1.7 A																																												
Capacitor size - run:	10 µF/180 V																																												
Number of poles:	2																																												
Insulation class (IEC 85):	F																																												



Company name:

Created by:

Phone:

Date:

9/13/2019

Count	Description
	<p data-bbox="225 338 319 369"><b>Others:</b></p> <p data-bbox="225 369 671 405">Gross weight: 5.22 kg</p>