



**BUILT WITH PRIDE
IN THE U.S.A.**

FROM OUR COMPACT STUBBY FLUORESCENT LIGHT, UP TO OUR 25-WATT FLUORESCENT SAF-T-LITE®, YOU CAN BE ASSURED THESE LIGHTS ARE DESIGNED TO LAST! THE ON-OFF SWITCH LOCATED UNDER THE DOMED END CAP IS PROTECTED FROM DIRT AND MOISTURE. THE POLYCARBONATE OUTER TUBE IS BREAK RESISTANT. SOFT END CAPS AT EACH END HELP ABSORB IMPACTS DURING ROUGH USE.

**COMPACT FLUORESCENT
STUBBY, 15 & 25 WATT**



Model No. 1413-2500

Model No. 1215-2500



Model No. 1225-2500

Features

- 13-WATT STUBBY®**
 - 10.5" COMPACT LENGTH.
 - ROUGH SERVICE BULB IS 10X MORE IMPACT RESISTANT THAN STANDARD BULBS AND CONTAINS ONLY TRACE MERCURY.
 - LIGHT OUTPUT IS 825 LUMENS OF BRIGHT 5000K COLORED LIGHT.
 - LAMP IS RATED FOR 10,000 HOURS.
- 15-WATT SAF-T-LITE®**
 - 22' LIGHT STRETCHES LIGHT OVER A LARGER AREA.
 - LIGHT OUTPUT IS 870 LUMENS OF BRIGHT 4100K COLORED LIGHT.
 - F15T8CW LAMP IS RATED FOR UP TO 7500 HOURS.
 - LAMP IS ULTRA-COOL OPERATING.
- 25-WATT SAF-T-LITE®**
 - 45" LIGHT MAXIMIZES LARGE LIGHT PATTERN.
 - LIGHT OUTPUT IS 2125 LUMENS OF BRIGHT 4100K COLORED LIGHT.
 - F25T8CW LAMP IS RATED FOR UP TO 20,000 HOURS.
 - LAMP IS COOL OPERATING.

CORD MODELS

Model No. Std. Tube	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Cord Specs	Case Qty.	Case Weight
1413-2500	Stubby	No	N/A	Yes	25'	18/2 SJTOW-A	12	36 lbs.
1413-2501	Stubby	No	N/A	No	25'	18/2 SJTOW-A	12	36 lbs.
1413-5000	Stubby	No	N/A	Yes	50'	18/2 SJTOW-A	12	72 lbs.
1215-2500	15 Watt	No	N/A	Yes	25'	18/2 SJTOW-A	12	43 lbs.
1225-2500	25 Watt	No	N/A	Yes	25'	16/3 SJTOW-A	4	20 lbs.
1225-2501	25 Watt w Straps*	No	N/A	Yes	25'	16/3 SJTOW-A	4	23 lbs.

* 25 W HOODLIGHT COMES WITH ADJUSTABLE HANGING KIT (5000-0851) ON PG 24.

REEL MODELS

Model No. Std. Tube	Description	Switch Y/N	Retracting Cord Specs	Pigtail Cord Specs	Cord Specs	Case Qty.	Case Weight
3215-4000	15-Watt, 40' Reel	Yes	40' 18/2	2' 16/3	SJTOW-A	4	44 lbs.
3313-4000	Stubby, 40' Reel	Yes	40' 18/2	2' 16/3	SJTOW-A	4	39 lbs.
3413-4000	Stubby Auto Reel	Yes*	40' 18/2	2' 16/3	SJTOW-A	4	39 lbs.

* SWITCH IS LOCATED ON THE REEL. PULL LIGHT DOWN TO TURN ON, RETRACT TO TURN LIGHT OFF.