

INSIZE		Inspection Certificate	
Product name	Outside Micrometer	Unit: inch	
Code No.	3203-1A	Measuring Length	Permissible Error
Measuring range	0-1"	0.000	0.0000
Graduation	0.0001"	0.210	0.0001
Serial No.	0910120004	0.420	-0.0001
Standard temperature	68 °F	0.605	0.0000
Based on	ASME B89.1.13-2013	0.815	-0.0001
Traceable to	USA NIST No.621/279484-10	1.000	0.0001
Inspector	<i>Paulo</i>	Judgement:	Passed

MANUFACTURER INSPECTION CERTIFICATE TRACEABLE TO NIST, FOR MICROMETERS

5

ELECTRONIC OUTSIDE MICROMETERS



- Resolution .00005"/0.001mm
- Button functions: on/off, set, inch/mm, ABS/INC
- No data output
- LR44 battery, automatic power off
- Carbide measuring faces
- Friction thimble
- Supplied with spherical anvil
- Setting standards are included (except 0-1"/0-25mm)

ATTENTION: NO
DATA OUTPUT

INSPECTION
CERTIFICATE
TRACEABLE TO NIST



3109-25E



Part No.	Range	Accuracy	L	a	b
3109-25E *	0-1"/0-25mm	±.00010"	1.260"	.236"	1.083"
3109-50E *	1-2"/25-50mm	±.00015"	2.244"	.315"	1.457"
3109-75E *	2-3"/50-75mm	±.00015"	3.228"	.315"	1.969"
3109-100E *	3-4"/75-100mm	±.00015"	4.213"	.394"	2.402"

* Supplied with manufacturer inspection certificate traceable to NIST


OUTSIDE MICROMETERS WITH COUNTER

- Counter resolution .001"
- Thimble graduation .0001"
- Carbide measuring faces
- Ratchet stop
- Supplied with setting standards (except 0-1")

INSPECTION
CERTIFICATE
TRACEABLE TO NIST



3400-1




Part No.	Range	Accuracy	L	a	b
3400-1 *	0-1"	.00016"	1.260"	.236"	1.024"
3400-2 *	1-2"	.00016"	2.244"	.315"	1.260"
3400-3 *	2-3"	.00020"	3.228"	.315"	1.752"
3400-4 *	3-4"	.00020"	4.213"	.315"	2.244"

* Supplied with manufacturer inspection certificate traceable to NIST

OUTSIDE MICROMETERS FOR LEFT OR RIGHT HAND

- Graduation .001"
- Graduations on two sides
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards (except except 0-1")



front



back

3236-1B

Part No.	Range	Accuracy	L	a	b
3236-1B	0-1"	.00016"	1.260"	.236"	.945"
3236-2B	1-2"	.00016"	2.244"	.315"	1.260"
3236-3B	2-3"	.00020"	3.228"	.315"	1.752"