

Pony Hold-Down Clamps

- Offers the advantage of bench top and machine surface clamping
- For use on machine table slots or wherever t-slots or machine bolt mounting is available
- Rotates 360 degrees around the holding bolt



HEAVY-DUTY HOLD-DOWN CLAMP

Heavy-duty hold-down clamps are designed for mounting anywhere a t-slot or machine bolt can be installed. These clamps offer the advantage of bench-top and machine table "surface" clamping. Rotates 360° around the bolt and can be mounted on wood or metal surfaces. A unique square-head screw offers wrench tightening for secure hold.

NO	OPENING	THROAT DEPTH	LOAD LIMIT
1834	4"	2-1/2"	6000lbs

BENCH HOLD-DOWN CLAMP

A versatile, easy-to-use clamp for holding work in place on bench tops. Made of solid iron with a black baked enamel finish; holds work securely by simply tapping into hole in bench top (requires pre-drilling).



- Versatile and easy to use clamp for holding work in place on bench tops
- Holds work securely by simply tapping into a pre-drilled hole in bench top
- Solid iron with a black baked enamel finish

NO	LENGTH	REACH	PRE-DRILLING HOLE
1708	8"	4"	11/16"
1716	16"	8"	13/16"

Pony Hold-Down Clamps

- Offers the advantage of bench top and machine surface clamping
- Use anywhere on wood or metal surfaces
- Rotates 360 degrees around the holding bolt



HOLD-DOWN CLAMP

Hold-down clamps offer the advantage of benchtop and machine "surface" clamping. They are designed to rotate 360° around the holding bolt. Use anywhere on wood or metal surfaces.

NO	OPENING	THROAT DEPTH	LOAD LIMIT
1623	3"	1-3/4"	2000lbs
1623-BA	Accessory		

Pony Spring Clamps

Spring Clamp with protective handles & tips



Spring action allows instant opening and closing where fast, easy application to or removal from the work is required and where spring pressure is adequate. Handle contours enable comfortable use. Non-slip jaws become parallel at maximum opening capacities. Poly-vinyl "protected" handles and/or jaw tip are available in all sizes. Point-of-pressure always remains near jaw tips throughout the entire range of openings, to hold where needed.

1. One of the most durable clamps available
2. Non-slip jaws become parallel at maximum opening capacities
3. Light weight, zinc plated steel jaws



NO	PROTECTED HANDLE & TIPS	MAX. OPENING	REACH
3201	Without	1"	1-1/4"
3201-HT	With	1"	1-1/4"
3202	Without	2"	2"
3202-HT	With	2"	2"
3203	Without	3"	3"
3203-HT	With	3"	3"
3204-HT	With	4"	4"