

Tool Accessories

Primark Tool Group

Primark Tool Group


SCREWDRIVER BITS

Parts and Types of Screwdriver Bits

Insert Bits are compact bits that are economical, change over quickly and require less storage space and require a bit holder.



They are 1" OAL (overall length) with 1/4", 3/16", & 5/16" hex shanks.



Power Bits fit directly into the power tool for improved concentricity and easier clearance. They are 1-15/16" - 6" or longer OAL (overall length) with 1/4" and 5/16" hex shanks.



General Information:



Nutsetters: Popular for the pre-engineered building industry. For use with Hex Head Screws. 1/4" Hex Shank.

Bit Holders: To be used in conjunction with insert bits. "C" Ring retainer and magnetic. One or two piece construction.

Extensions/Socket Adapters: Adapts a handriver or drill into a socket wrench.

Finding the Right Phillips® Bit

Locate the size and type of screw you will be driving in the chart below. Then move to the far right column to find the right point size for the Phillips you need.

Wood Screw Size		Machine Screw Size		Sheet Metal Screw Size	Point Size
Flat	Round	Flat Oval	Round	Truss	Flat, Oval
Oval	Round	Binding	Fillister	Brazier Button	Round, Stove Binding
0,1	0,1	0,1	0,1	0,1	0
2,3,4	2,3,4	2,3,4	2,3,4	2,3,4,5	1
5,6,7,8,9	5,6,7,8,9,10	5,6,8,10	5,6,8,10	6,8,10	2
10,12,14,16	12,14,16	12,1/4	12,1/4	12,1/4	3
18,20,24	18,20,24	5/16,3/8,7/16,1/2	3/8,7/16,1/2	5/16,3/8,7/16,1/2	4

Tri-Wing®, POZIDRIV®, Torq-Set®, Phillips Square Drive® and Phillips® is a registered trademark of the Phillips Screwdriver Company.

Quadrex® is a registered trademark of Isotech Consultants, Inc.

Torx® is a registered trademark of Camcar Division of Textron.

Phillips® Insert Bits

- Special bit design absorbs torque peaks reducing slippage and breakage.
- Reduced diameter tip and ribs reduce cam-out and drywall damage.
- Cold formed for optimum toughness and resistance to wear.
- Most widely used style.
- Many configurations and hardnesses.



Ribs: The interlocking ribs of the system provide higher torque. Components in the system are interchangeable with standard Phillips components.

Drywall Bits – 1/4" Hex Shank

Part No. Bulk	App.	Hardness	Point Size	Overall Lgth. (In)	Std. Shp. Pack
24203	Drywall	Extra-Hard	P2, Rib	1	1
24206	Drywall	Extra-Hard	Sq. Rec. #2	1	1

Decking/Subflooring Bits – 1/4" Hex Shank

Part No. Bulk	App.	Hardness	Point Size	Overall Lgth. (In)	Std. Shp. Pack
24303	Decking/Subflooring	Extra-Hard	P2, Rib	1	1

1/4" Hex Shank

Pl. No. Med. Hard	Pl. No. Extra Hard	Pl. No. Ex. Hard	Pl. No. Iso-Temp™	Pl. No. Iso-Temp Ribs	Overall Length (In)	Point Size	Std. Shp. Pack
*	27019	*	45143	*	1	0	1
25020	27020	46004	45189	45912	1	1	1
25021	27021	46005	45190	45913	1	2	1
25022	27022	*	45191	45914	1	3	1
*	27023	*	35348	*	1-1/2	2	1
*	27024	*	35349	*	2	2	1
*	27025	*	35350	*	2-1/2	2	1
*	*	*	35360	*	2	0	1
*	*	*	35358	*	2	1	1
*	*	*	35359	*	2	3	1
*	*	*	35894	*	1-1/8	4	1
*	48428 milled	*	*	*	1	1	1
*	48429 milled	*	*	*	1	2	1
*	48430 milled	*	*	*	1	3	1

– Reduced Diameter – 1/4" Hex Shank

Pl. No. Med. Hard	Pl. No. Extra Hard	Pl. No. Ex. Hard	Pl. No. Iso-Temp™	Pl. No. Iso-Temp Ribs	Overall Length (In)	Point Size	Std. Shp. Pack
*	27018	*	*	*	1	OR	1
*	27035	*	35351	*	1	1R	1
25036	27036	45339	44963	45333	1	2R	1

– Reduced Diameter (.187) Extra Length – 1/4" Hex Shank

Part No. Ex. Hard	Overall Lgth. (In)	Point Size	Std. Shp. Pack
37513	2	1	1
37514	2	2	1
37515	3	2	1

5/16" Hex Shank

Part No. Ex. Hard	Part No. Iso-Temp™	Overall Lgth. (In)	Point Size	Std. Shp. Pack
27206	35352	1-1/4	1	1
27206	35353	1-1/4	2	1
27207	48280	1-1/4	3	1
27208	35354	1-1/4	4	1

Phillips Square Drive® – 1/4" Hex Shank

- Compatible with Quadrex screwheads.
- Ribbed tips.

Part No. Ex. Hard	Overall Lgth. (In)	Point Size	Std. Shp. Pack
35888	1	PSD2-2, Rib	1