

Generous bevel

on striking face

Handle "Sure-Lock®"

wedged in eye

HAND DRILLING HAMMER
The right hammer for striking star drills, cold chisels, brick chisels and punches. Broad, polished striking faces with generous bevels. Rust resistant black finish on smooth ground sides. Select, flame treated hickory handle.

| | CODE | CATALOG NO. | HEAD \ | NEIGHT ka | LGTH. in. | STD. PKG. | PKG. lbs. | | |
|---|--------------------------------|----------------|--------|--------------|---------------|--------------|--------------|--|--|
| | OODL | 140. | 10. | кg | 1111. | r Ku. | ibs. | | |
| | 191-10 | HD3 | 3 | 1.4 | 101/4 | 4 | 14 | | |
| , | Solid Steel Handle (Not Shown) | | | | | | | | |
| | 190-10 | RHD3 | 21/2 | 1.1 | $10^{3}/_{4}$ | 4 | 14 | | |

HEAVY HITTERS™ BLACKSMITH & **DOUBLE FACE HAMMERS**

Fiberglass handles are fitted with high-impact rubber overstrike shields in the critical neck area; patented hollow core handle and slip-resistant, cushioned PVC grip absorb shock. Flame treated hickory handles are "Sure-Locke" wedged in tapered eve

| weagea | in tapered e | ye. | | | | | | |
|---|------------------------------------|-------------|--------------|--------------|--------------|--------------|--|--|
| ITEM CODE | CATALOG NO. | HEAD lb. | WEIGHT kg | LGTH. in. | STD. PKG. | PKG. lbs. | | |
| Blacksmith Hammers-Fiberglass Handles (Not Shown) | | | | | | | | |
| 171-20 | S40F | 21/2 | 1.1 | 15 | 4 | 131/2 | | |
| 172-20 | S48F | 3 | 1.4 | 15 | 4 | 131/2 | | |
| Blacksn | Blacksmith Hammers-Hickory Handles | | | | | | | |
| 170-30 | S32 | 2 | 0.9 | 141/2 | 4 | 10 | | |
| 171-30 | S40 | 21/2 | 1.1 | 151/2 | 4 | 121/2 | | |
| 172-30 | S48 | 3 | 1.4 | 16 | 4 | 15 | | |
| Double Face Hammers-Fiberglass Handles | | | | | | | | |
| 173-20 | SDF40F | 21/2 | Ĭ.1 | 15 | 4 | 131/2 | | |
| 181-20 | SDF48F | 3 | 1.4 | 151/4 | 4 | 16 | | |
| 571-20 | SDF64F. | 4 | 1.8 | 151/2 | 2 | 91/2 | | |
| Double Face Hammers-Hickory Handles | | | | | | | | |
| 173-30 | SDF40 | 21/2 | 1.1 | 151/2 | 4 | 121/2 | | |
| 174-30 | SDF48 | 3 | 1.4 | 16 | 4 | 15 | | |



Encourage safe work habits! Advise your customers to always wear safety goggles when using striking tools.



CODE NO. lb. in. PKG lbs. kg 175-10 21/4 L36 1.0 151/2 11 LINEMAN'S STRAIGHT CLAW HAMMER (Not Shown)

Drop forged from high carbon steel. Polished striking face, extra thick straight claws. Flame treated hickory handle, "Sure-Lock" wedged in tapered eye.

| CODE | CATALOG NO. | HEAD \ lb. | WEIGHT kg | | STD. PKG. | PKG. lbs. |
|--------|----------------|------------|--------------|-------|--------------|--------------|
| 107-14 | LSC32 | 2 | 0.9 | 151/4 | 2 | 6 |

INDUSTRIAL MAULS

Drop forged from high carbon steel and annealed only, not hardened. Intended for use where hardened steel hammers would damage steel parts. Polished faces and bevels, rust resistant black finish on sides. Exclusive hollow core fiberglass handle with neoprene grip absorbs shock. Epoxy sealed assembly.

| ITEM | CATALOG | HEAD Ib. | WEIGHT | LGTH. | STD. | PKG. |
|--------|---------|----------|--------|-------|------|------|
| CODE | NO. | | kg | in. | PKG. | Ibs. |
| 188-55 | M1½F | 1½ | 0.7 | 15 | 4 | 7 |
| 189-55 | M3F | 3 | 1.4 | 15 | 4 | 13 |

DOUBLE FACE SLEDGES (Not Shown)

Polished faces with generous bevels. Rust resistant black finish on sides. Flame treated hickory handle.

| in horr orr oraco: r larrio troatou rhortory riarialo. | | | | | | | | |
|--|---------|--------|--------|-------|------|------|--|--|
| ITEM | CATALOG | HEAD ' | WEIGHT | LGTH. | STD. | PKG. | | |
| CODE | NO. | | kg | in. | PKG. | Ibs. | | |
| 571-04 | SS4 | 4 | 1.8 | 16 | 2 | 9 | | |
| 571-06 | SS6 | 6 | 2.7 | 36 | 2 | 13 | | |
| 571-08 | SS8 | 8 | 3.6 | 36 | 2 | 17 | | |
| 571-10 | SS10 | 10 | 4.5 | 36 | 2 | 21 | | |
| 571-12 | SS12 | 12 | 5.5 | 36 | 2 | 25 | | |
| | | | | | | | | |