

Opalia™ Whirlpool Bath

BN05 Opalia™ Whirlpool Bath Left Hand
BN15 Opalia™ Whirlpool Bath Left Front Pump
DA39 Opalia™ Whirlpool Bath Left Back Pump
BN00 Opalia™ Whirlpool Bath Right Hand
BN10 Opalia™ Whirlpool Bath Right Front Pump

Opalia™ Bath

9635 Opalia™ Bath

• Center Drain Location

Accessories / Hardware:

Trip-Lever Drain Kit #X559 Rotary Drain Kit, 26" Cable #8730 TheraPro Jet Trim Kit: #D095 AccuPro Jet Trim Kit: #P555

• Trim Kit Finishes Available:

(827) - Chrome

(826) - Brushed Nickel

(849) - Oil Rubbed Bronze

72" 13" X 4" 32" 12" H x 18" L Service Access 4" 4-11/16" 36"

Product Shown: Opalia™ Whirlpool Bath Left Hand Shown Model: BN05

INSTALLATION NOTES

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Technical Specifications

DIMENSIONS

72" L x 44" W x 22-1/4" H (1829 mm) L x (1118 mm) W x (565 mm) H

DRAIN/OVERFLOW

A: 18-3/4" (476 mm) B: 12" (305 mm)

CUTOUT

Template Provided P/N GN52000

TOTAL WEIGHT

BN00: 978 lb (445 kg) / 45 lb/sq. ft. (217 kg/m²) BN05: 945 lb (429 kg) / 45 lb/sq. ft. (217 kg/m²) 9635: 945 lb (429 kg) / 43 lb/sq. ft. (210 kg/m²)

OPERATING GALLONAGE

70 U.S. Gal. (265 Liters)

PRODUCT WEIGHT

BN00, BN05: 145 lb (66 kg) 9635: 112 lb (51 kg)

SKIRT MOUNTING


Not Available


ELECTRICAL SPECIFICATIONS MODELS BN00, BN05 ONLY Requires a dedicated GFCI protected separate circuit.


Motor/Pump: 120 VAC, 15 AMP, 60 Hz. RapidHeatTM: 120 VAC, 15 AMP, 60 Hz.

HEATER (OPTIONAL) MODELS BN00, BN05 ONLY Requires a dedicated GFCI protected separate circuit.

RapidHeat™: P/N S750000







^{*} Measurements inside unit represent cutout in floor to allow for drain/overflow.