



### **Product specifications**

#### **• 5-3/4" Projection**

- rigid, thermally insulated outlet
- Laminar stream
- Total height 11-3/8"
- 7-1/8" height to aerator/spout outlet
- 1-3/8" hole diameter
- Provides filtered, hot water, 199°F max. temperature
- Provides filtered, cold water (not chilled)
- Water flow rate limited to max. 0.5 gpm
- control unit for wall assembly (5-3/8" x 6-1/4" x 2-3/8")
- electronic valve
- plug-in power supply, 100-230 V, 50-60 Hz, 18 W, incl. country-specific adaptor set
- low lead compliant
- One lever for hot and cold water

#### **(ADA)**

**Compatible with Insinkerator® hot water tank HWT-F1000S. Tank and filter not supplied from Dornbracht. More information on tank and filter at [www.inksinkerator.com](http://www.inksinkerator.com).**

**We recommend replacing the filter cartridge every six months. Please see the installation manual for more information.**

Kitchen

**Water Dispenser HOT & COLD WATER DISPENSER**

Article number: 17 861 888



**All Professional information and detailed notes  
regarding planning can be found at  
[www.dornbracht.com](http://www.dornbracht.com)**

**Surfaces**

- chrome 17861888-00
- matt platinum 17861888-06
- Cyprum 17861888-49