	FEATU	RES		
		Wattage 1.4	• The fitting is supplied with a collar and can be either surface or recess mounted	
			 Surface Light Source (SLS) products are LED fittings with no visible LED points 	
•7		Connector ML	 Aluminum finish available with either cool white or warm white LED - great for both contemporary and traditional kitchens 	
		Dimmable Yes	 Use as task lighting under cabinets or to illuminate cabinet interiors of glass cabinets 	
	J	<mark>Lifespan</mark> 50,000 hours	 Over 90% less energy used when comparing to halogen - save money on electricity bills when switching from halogen to LED 	
	•	Certification UL	Long lamp life - lasts up to 28 years more than halogen	
			Can be used with the range of Sensio switches and dimmers	
SV0012				

3A9U I Z

SLS LED Recess/Surface Light - This discreet SLS LED fixture has 6 high output LED diodes and can be surface mounted with included ring, or flush mounted. Thanks to the unique manufacturing process of the SLS range, they produce an even glow without individual LED's being visible. The convenient design allows this fixture to tuck out of the way or be mounted on almost any flat surface. The substantial thermoplastic construction assures years of enjoyment. The long life span of 50,000 hours provides years of maintenance-free lighting. Extremely low power usage allows for many hours of guilt-free task or display lighting, and does so without generating excessive heat. The SA9012 can be used with Sensio's dimmable driver which enables you to dim the puck lights using standard wall dimmer switches. This puck can also be used with standard drivers and the Sensio 4-zone wireless controller system to achieve dimming. Available in cool white or warm white light with an aluminum finish.

SPECIFICATIONS

Product Code	Voltage	LED Qty	LED Color	Temperature	Lumens	Beam	Cable	Hole Cut	Length	Width	Depth
SA9012WH	2 4V	6	Cool White	5,000K	95 (68 LPW)	120°	8.2' (2.5m)	56mm	2.7" (68.6mm)	2.7" (68.6mm)	0.6" (16mm)
SA9012WW	2 4V	6	Warm White	3,000K	90 (64 LPW)	120°	8.2' (2.5m)	56mm	2.7" (68.6mm)	2.7" (68.6mm)	0.6" (16mm)

DRIVERS			ACCESSORIES			
Product Code	Description	Wattage	Ports	Product Code	Description	Length
SA40654	24V non-dimmable driver with ML block	6W	4	SA9009	ML Extension Cable	8.2' (2.5m)
SA40655	24V non-dimmable driver with ML block	20W	12			
SA40656	24V non-dimmable driver with ML block	30W	12			
SA40651	24V dimmable driver with ML block	40W	12			