




Buy it for looks. Buy it for life.®

# Specifications



## WYNFORD™ Single-Handle Lavatory Faucet

Models: 4507 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE  
INSTALLED THRU 1 HOLE, 1-1/4" MIN. DIA.



### DESCRIPTION

- Metal construction with various finishes identified by suffix
- 24" Flexible supplies with 3/8" compression fittings

### OPERATION

- Temperature controlled by 100° arc of handle travel


### FLOW

- Water usage is limited to these maximum flow rates as indicated by the corresponding product markings
- ° 1.2 gpm max (4.5L/min) at 60 psi

### CARTRIDGE


- 1255™ Duralast™ cartridge for Single-Handle Faucets

### STANDARDS

- Third party certified to WaterSense,® ASME A112.18.1/CSA B125.1, and all applicable requirements referenced therein
- Certified to NSF 61/9 & 372
- Products marked with 1.2 gpm are compliant with California water efficiency regulations
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- **ADA**  for lever handle

### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com