GRINDING WHEELS / BLADES



Depressed Center Wheels

The depressed center design allows the flange/lock nut to recess within the wheel so that it can be used for various grinding and cutting applications. Depressed center wheels are designed to handle the most severe right angle grinding applications, from heavy stock removal to rough blending. Depressed center wheels may also be referred to as raised hub wheels or by their shape designation of "Type," with Type 27 being the most popular.

1/4" are designed for grinding:

- offhand stock removal of all types of metal and masonry
- smoothing welds
- pipe beveling

1/8" are designed to be used for both light grinding or cutting:

- offhand cut-off of all metal and masonry materials
- notching or cleaning pipes and weld beads

.125" are designed to be used at a 90° angle for cutting only









Professionals Want Choices

Norton NorZon Plus is the highest performance line in the industry. Invented and made in America, now improved and expanded.



Performance on Fire

Engineered with a proprietary NorZon grain upgrade, the Norton BlueFire design offers faster removal rate, longer product life and increased productivity for better performance value.



The Right Choice Every Time

The re-engineered Norton Gemini RightCut 100% aluminum oxide wheels provide thinner, faster cutting with a burr-free, precision cut and improved operator comfort.

| PART # | UPC-A | SIZE | MAX RPM | WHLS/ CASE | | |
|--|-----------------------|--------------------------------|------------|---------------|--|--|
| Accessory Fo | r Right Angle Grii | nders - Handy Packs | | | | |
| Adaptor Kit | | | | | | |
| 07660789275 | 076607 89275 1 | Adaptor kit for 7" & 9" wheels | N/A | 1 | | |
| Depressed Center Wheels (Type 27) - Bulk - UPC Bar Coded | | | | | | |
| Metal - NorZo | n Plus, For Grind | ing | | | | |
| 66252842178 | 662528 42178 3 | 3" x 1/4" x 3/8" | 18000 | 25 | | |
| 66252842002 | 662528 42002 1 | 4" x 1/4" x 3/8" | 15280 | 25 | | |
| 66252842003 | 662528 42003 8 | 4" x 1/4" x 5/8" | 15280 | 25 | | |
| 66252843328 | 662528 43328 0 | 4-1/2" x 1/4" x 7/8" | 13580 | 25 | | |
| 66252843326 | 662528 43326 6 | 4-1/2" x 1/4" x 5/8"-11 | 13580 | 10 | | |
| 66252843334 | 662528 43334 1 | 5" x 1/4" x 7/8" | 12225 | 25 | | |
| 66252843332 | 662528 43332 8 | 5" x 1/4" x 5/8"-11 | 12225 | 10 | | |
| 66252809376 | 662528 09376 8 | 6" x 1/4" x 7/8" | 10185 | 20 | | |
| 66252917880 | 662529 17880 8 | 7" x 1/4" x 7/8" | 8600 | 20 | | |
| 66252917881 | 662529 17881 5 | 7" x 1/4" x 5/8"-11 | 8600 | 10 | | |
| 66253021633 | 662530 21633 9 | 9" x 1/4" x 7/8" | 6600 | 20 | | |
| 66253021634 | 662530 21634 6 | 9" x 1/4" x 5/8"-11 | 6600 | 10 | | |
| | | | | | | |

| PART # | UPC-A | SIZE | MAX RPM | WHLS/ CASE | | | |
|---|-----------------------|-----------------------------|------------|---------------|--|--|--|
| | | e 27) - Bulk - UPC Bar Code | | 0.101 | | | |
| | | Grinding and Cutting | | | | | |
| 66252842177 | 662528 42177 6 | 3" x 1/8" x 3/8" | 18000 | 25 | | | |
| 66252842004 | 662528 42004 5 | 4" x 1/8" x 3/8" | 15280 | 25 | | | |
| 66252842005 | 662528 42005 2 | 4" x 1/8" x 5/8" | 15280 | 25 | | | |
| 66252843324 | 662528 43324 3 | 4-1/2" x 1/8" x 7/8" | 13580 | 25 | | | |
| 66252843323 | 662528 43323 6 | 4-1/2" x 1/8" x 5/8"-11 | 13580 | 10 | | | |
| 66252843331 | 662528 43331 0 | 5" x 1/8" x 7/8" | 12225 | 25 | | | |
| 66252938854 | 662529 38854 2 | 7" x 1/8" x 7/8" | 8600 | 20 | | | |
| 66252938855 | 662529 38855 9 | 7" x 1/8" x 5/8"-11 | 8600 | 10 | | | |
| 66253048896 | 662530 48896 5 | 9" x 1/8" x 7/8" | 6600 | 20 | | | |
| 66253048897 | 662530 48897 2 | 9" x 1/8" x 5/8"-11 | 6600 | 10 | | | |
| Metal - NorZor | Plus, For Pipe | Notching | | | | | |
| 66252939184 | 662529 39184 9 | 7" x 1/8" x 5/8"-11 | 8600 | 10 | | | |
| 66253049066 | 662530 49066 1 | 9" x 1/8" x 5/8"-11 | 6600 | 10 | | | |
| Depressed Center Wheels (Type 27/42) - Bulk - UPC Bar Coded | | | | | | | |
| Metal - NorZor | ı Plus, For Cuttii | ng Only | | | | | |
| 66252842001 | 662528 42001 4 | 4" x .125" x 3/8" | 15280 | 25 | | | |
| 66252843322 | 662528 43322 9 | 4-1/2" x .125" x 7/8" | 13580 | 25 | | | |
| 66252843321 | 662528 43321 2 | 4-1/2" x .125" x 5/8"-11 | 13580 | 10 | | | |