

Aluminum Reducing Bushings for Flap and Convolute Wheels



- Durable, aluminum one-piece-design flanges with integrated contact washer
- Snug fit; extended usable life
- Available in stock and non-stock sizes in many combinations of ID hole reduction

WHEEL CENTER HOLE	BUSHING REDUCES HOLE SIZE TO	FOR WHEEL DIAMETER	STD. PKG.	PART #
1	3/8	4 - 6	1 Pair	662610 80522 NS
	1/2	4 - 6	1 Pair	662610 80523
	5/8	4 - 6	1 Pair	662610 80524
	3/4	4 - 6	1 Pair	662610 80525 NS
2	7/8	4 - 6	1 Pair	662610 80526 NS
	1	6	1 Pair	662610 80527 NS
3	5/8	6	1 Pair	662610 80528 NS
	1	6	1 Pair	662610 80529 NS
5	1	8	1 Pair	662610 80531
	1-1/4	8	1 Pair	662610 80532
8	1	10 and 12	1 Pair	662610 80533
	1-1/4	10 and 12	1 Pair	662610 80534
	3	10 and 12	1 Pair	662610 80535 NS
8	1-1/4	14	1 Pair	662610 80536 NS

NS Non-Stock, contact your Norton representative for current order quantities and lead times.

TECH TIP

- Convolute wheels must always run in the direction indicated by the arrow printed on the side of each wheel.
- Light to medium pressure is recommended. Excessive pressure may result in part damage.
- Lubricants such as water-soluble oil and straight oil will decrease the heat and improve the surface finish and lustre.



It is the user's responsibility to refer to and comply with ANSI B7.1