

SAFETY DATA SHEET

1. Identification

Product identifier Oatey H2O 95 Tinning Flux

Other means of identification

SDS number 1614E

Synonyms Part Numbers: 301410, 30142, 30143, 53068, 53073

Recommended use Joining Copper Pipes. Joining Copper Tubing.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name Oatey Co.

Address 4700 West 160th St.

Cleveland, OH 44135

Telephone 216-267-7100 info@oatey.com

Transport Emergency Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

Emergency First Aid 1-877-740-5015
Contact person MSDS Coordinator

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSkin corrosion/irritationCategory 1B

Serious eye damage/eye irritation Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage.

Precautionary statement

Prevention Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face

protection. Do not breathe dusts or mists.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Glycerin	56-81-5	6-12

Oatey H2O 95 Tinning Flux SDS US

922601 Version #: 04 Revision date: 19-February-2015 Issue date: 11-November-2014

Triethanolamine Hydrochloride	637-39-8	6-12
Tin	7440-31-5	4-8
Zinc chloride	7646-85-7	2-8
Ammonium chloride	12125-02-9	1-5
Bismuth	7440-69-9	0.1-1
Copper	7440-50-8	0.1-1

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. Call a

physician or poison control center immediately. Remove contact lenses, if present and easy to do.

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delayed

blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike far ahead of spill for later disposal. Cover with plastic sheet to prevent spreading.

Small Spills: Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Oatey H2O 95 Tinning Flux SDS US

7. Handling and storage

Precautions for safe handling Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not get this material on clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe

good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table 7-1 Limits for Air Contaminants (29 CER 1910 1000)

Components	Туре	Value	Form
Copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Glycerin (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Tin (CAS 7440-31-5)	PEL	2 mg/m3	
Zinc chloride (CAS 7646-85-7)	PEL	1 mg/m3	Fume.
US. ACGIH Threshold Limi	t Values		
Components	Туре	Value	Form
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.
	TWA	10 mg/m3	Fume.
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.
	TWA	1 mg/m3	Fume.
US. NIOSH: Pocket Guide	o Chemical Hazards		
Components	Туре	Value	Form
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.
	TWA	10 mg/m3	Fume.
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.
	TWA	1 mg/m3	Fume.
ogical limit values	No biological exposure limits noted for the ingredient(s).		
osure guidelines	Occupational Exposure Limits are not relevant to the current physical form of the product.		
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits.		

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Other

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Always observe good personal hygiene measures, such as washing after handling the material General hygiene and before eating, drinking, and/or smoking. Routinely wash work clothing and protective considerations

exposure limits have not been established, maintain airborne levels to an acceptable level. Eye

wash facilities and emergency shower must be available when handling this product.

equipment to remove contaminants.

Oatey H2O 95 Tinning Flux SDS US

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid. Paste.

Color Gray.
Odor Slight.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure > 1

Vapor density Not available.

Relative density 1.3

Solubility(ies)

Solubility (water) Soluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity20000 - 40000 cP

Other information

VOC (Weight %) 7 g/l <1% by weight

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Chlorine.

Hazardous decomposition

products

Decomposition may yield acrolein. No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. May cause irritation to the respiratory system.

Skin contactCauses severe skin burns.Eye contactCauses serious eye damage.IngestionCauses digestive tract burns.

Oatey H2O 95 Tinning Flux SDS US

922601 Version #: 04 Revision date: 19-February-2015 Issue date: 11-November-2014

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Copper (CAS 7440-50-8)		
Acute		
Inhalation		
LC50	Rat	> 2.77 mg/l, 4 hours
Oral		
LD50	Rat	481 mg/kg
Glycerin (CAS 56-81-5)		
Acute		
Oral		
LD50	Rat	12600 mg/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

Serious eye damage/ey

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Causes serious eye damage.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure. None known.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow) Glycerin (CAS 56-81-5)

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

-1.76

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Oatey H2O 95 Tinning Flux SDS US

922601 Version #: 04 Revision date: 19-February-2015 Issue date: 11-November-2014

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium chloride (CAS 12125-02-9)

Copper (CAS 7440-50-8)

Zinc chloride (CAS 7646-85-7)

LISTED

LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Zinc chloride	7646-85-7	2-8
Ammonium chloride	12125-02-9	1-5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Ammonium chloride (CAS 12125-02-9)

Copper (CAS 7440-50-8)

Glycerin (CAS 56-81-5)

Tin (CAS 7440-31-5)

Oatey H2O 95 Tinning Flux SDS US
922601 Version #: 04 Revision date: 19-February-2015 Issue date: 11-November-2014 6 / 7

Zinc chloride (CAS 7646-85-7)

US. New Jersey Worker and Community Right-to-Know Act

Ammonium chloride (CAS 12125-02-9)

Copper (CAS 7440-50-8) Glycerin (CAS 56-81-5) Tin (CAS 7440-31-5)

Zinc chloride (CAS 7646-85-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Ammonium chloride (CAS 12125-02-9)

Copper (CAS 7440-50-8) Glycerin (CAS 56-81-5) Tin (CAS 7440-31-5)

Zinc chloride (CAS 7646-85-7)

US. Rhode Island RTK

Ammonium chloride (CAS 12125-02-9) Copper (CAS 7440-50-8) Zinc chloride (CAS 7646-85-7)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 11-November-2014 **Revision date** 19-February-2015

Version # 04
HMIS® ratings Hea

United States & Puerto Rico

Health: 3 Flammability: 0

Physical hazard: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently

available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for use, handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Oatey H2O 95 Tinning Flux SDS US

922601 Version #: 04 Revision date: 19-February-2015 Issue date: 11-November-2014

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).