

HCC Holdings, Inc.

4700 West 160th
Cleveland, Ohio 44135

Phone: 800-321-9532
Website: www.Oatey.com



PLUMBERS CAULK™ Caulking

Date: August 2017

Plumbers Caulk is a high quality commercial grade product. Easy-to-use, single component, non-sag, siliconized acrylic-latex caulk. Excellent expansion-contraction and mildew-resistance properties. Plumbers caulk makes a flexible, durable, and UV resistant waterproof seal on interior and exterior surfaces. Will not crumble, resists shrinking, and can be painted. Cleans up easily with soap and water before it cures, flows easily from tube and cartridge, bonds to all common building materials, tools easily, is tack-free in one hour and has a 25 year life expectancy.

Available in four popular finishes: Bright white, clear, almond/bone and biscuit/linen to match contemporary colored fixtures.

Clear caulk applies white, dries crystal clear and is especially useful on high style marble, ceramic, metal and plastic installations where white or colored caulk would detract from appearance.

Do not apply below 40°F.



APPROVALS & LISTINGS

Not applicable

SPECIFIC USES

Use **Plumbers Caulk** to seal interior or exterior surfaces. Seals and fills cracks and holes around tubs, showers, sinks, vanities, on walls and door or window frames in bathrooms, kitchens, and laundry rooms.

SPECIFIC APPLICATIONS*

Plumbers Caulk may be used indoors or outdoors on building materials including wood, ceramic tile, concrete, metal, glass, stone, brick, plastic, tile, stucco, and marble.

*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com.

DIRECTIONS FOR USE

Preparation: Surfaces should be clean and dry. Remove loose grout, mortar, dust, and dirt with a dry brush or rag. Do not use solvents to clean joints unless surfaces can dry thoroughly before caulk application. Joint depth should not exceed 1/2". Remove overcap on nozzle and cut off tip for desired caulk thickness. For best results, apply when ambient temperature is at least 50°F (10°C).

Application: For tube, squeeze with steady pressure. For cartridge, apply with caulking gun. Bead may be smoothed with wet finger or tool before caulk dries. For tooling ease, keep tools moist with soapy water. Wipe off any excess caulk with damp cloth before it dries. Replace overcap after using. Allow to stand overnight before water contacts new caulk. Can be painted with latex or oil base paint after 24 hours.

Clean up: Wash hands, tools, and adjacent surfaces with soapy water before caulk dries.

Note: Some brands of caulk are packaged in the same size tubes and cartridges as Hercules and show a "Net Weight" which is close to Hercules "Fluid Measure". In all instances, the "Fluid Measure" package contains substantially more material. Compare package sizes. If they are the same, know that the one designating "Fluid Measure" gives you more.

PHYSICAL PROPERTIES

Solubility in water:	Soluble before curing
Durability:	Mildew resistant. Resists UV deterioration
Flexibility:	Withstands 121 /2% joint movement
Appearance/color:	White: Creamy paste Clear: Applies white, cures clear. Cure Time: A 1/4 inch bead dries clear in 36 hours at @ 76°F Almond/Bone: Creamy paste Biscuit/Linen: Creamy paste
Odor:	Mild acrylic odor (all four finishes)

WARNINGS OR CAUTIONS

- Read all cautions and directions carefully before using product.
- **KEEP OUT OF REACH OF CHILDREN.**
- DO NOT take internally.
- Avoid eye contact.
- Keep from freezing.
- Keep tube or cartridge capped when not in use.
- WEATHER PRECAUTIONS: As this is a water-based product it should not be exposed to freezing temperatures. Plumbers caulk will take longer to cure at lower temperatures and should not be applied below 40°F. Additionally, it should be applied at least one week before any freezing temperatures are anticipated. At temperatures above 70°F this product will typically resist normal rainfall after 8 hours

MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS)-White/Colors #7354E, Clear #7355E

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of www.Oatey.com

Clear:

HMIS® ratings Health: 1
 Flammability: 1
 Physical hazard: 0

White & Colors:

HMIS® ratings Health: 0
 Flammability: 1
 Physical hazard: 0

SIZE & PACKING

STOCK NUMBER	COLOR	SIZE	PACKING	WEIGHT/CASE
25605*	White	6 fl. oz.	24 (2-1 dz.)	16.5 lbs.
25615+	White	11 fl. oz.	12	15.0 lbs.
25620*	Clear	5.5 fl. oz.	24 (2-1 dz.)	16.5 lbs.
25625+	Clear	10.3 fl. oz.	12	15.0 lbs.
25631*	Almond/Bone	5.5 fl. oz.	24 (2-1 dz.)	16.5 lbs.
25636+	Almond/Bone	10.3 fl. oz.	12	15.0 lbs.
25641*	Biscuit/Linen	6 fl. oz.	24 (2-1 dz.)	16.5 lbs.
25646+	Biscuit/Linen	11 fl. oz.	12	15.0 lbs.
25641R	Linen	5.5 fl. oz.	24	

*Display + Cartridge