



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

TUB-N-TILE CAULK



TECHNICAL SPECIFICATION: Oatey Tub-N-Tile Caulk is a flexible, acrylic latex general purpose sealant recommended for caulking bathtubs, sinks, showers and lavatories. Tub-N-Tile Caulk can also be used on most common building products such as concrete, metal, wood, marble, glass and brick. Tub-N-Tile Caulk is mold and mildew resistant.



PHYSICAL/CHEMICAL PROPERTIES

Appearance	White
pH	9.0 ± 1.0
Tack Free Time	1 Hour
Full Cure	36 Hours
Shelf Life	1 year unopened
VOC Content	250 g/L maximum

DIRECTIONS FOR USE

Clean off any dirt or dust particles with water. Do not use soap. Using a utility knife, remove any remnants of old caulking. New caulk will not adhere well to previously cured caulk. Once all caulk residue is removed, clean the area with a mild abrasive or rubbing alcohol. Use a concentrated mildew remover if the area shows signs of mildew. With a 45° angle, cut the tapered nozzle of the caulk tube to the width required to fill the crack or joint. Hold the tube at a 45 angle and use even pressure to apply caulk. Move the tube at an even pace along the joint to be filled. If the bead of caulk is too narrow, re-cut the nozzle to provide a larger opening. Allow the caulk to set for sufficient time. Product should be protected from water for a minimum of 8 hours to allow initial curing. Tub-N-Tile Caulk can be applied at temperatures between 40°F to 90° F. Full clarity of sealant is reached in 3 to 7 days. Sealant may be painted over with latex or oil based paint one hour after sealant is tack-free.

PRECAUTIONS

High vapor concentrations may cause headache, dizziness and nausea. Prolonged or repeated skin contact may lead to drying and irritation. Eye contact may cause irritation.

FIRST AID: If swallowed- Contact physician or poison control center immediately. Eye Contact- Flush eye with copious amounts of water while holding eyelid open. Contact physician if irritation persists. Skin Contact- Wipe material from skin with clean cloth or paper towel. Wash exposed area with soap and water. Contact physician if irritation persists. If inhaled- Seek fresh air. Keep container closed when not in use. **DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.**

Refer to material safety data sheet for more information. For emergency first aid help, call 1-303-623-5716 COLLECT.

COMMON APPLICATIONS

Oatey Tub-N-Tile Caulk is a flexible, acrylic latex general purpose sealant recommended for caulking bathtubs, sinks, showers and lavatories. Tub-N-Tile Caulk should not be used on copper or brass as discoloration may result. Service Temperature Range for sealant is 0° F to 200° F.

Consult Oatey Technical Department for applications not specifically referenced above.

HAZARDOUS INGREDIENTS (CAS Number)

- Mineral Spirits (8052-41-3)
- Ethylene Glycol (107-21-1)
- Butyl Benzyl Phthalate (85-68-7)

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
30240	6 oz. Tub-n-Tile Caulk – Tube	24	14 lbs.
30241	10 oz. Tub-n-Tile Caulk – Cartridge	24	18 lbs.