

Oatey® 4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

LIQUILOCK™ BY OATEY GEL



TECHNICAL SPECIFICATION

TECHNICAL SPECIFICATION: Oatey LiquiLock Gel will solidify water in the toilet bowl providing a clean, fast and easy method for removal of the toilet. Quick acting LiquiLock Gel formula will solidify residual water in the toilet bowl within 4-5 minutes. The toilet bowl water will remain in a gel form during removal period and will dissolve when additional water is added.



PHYSICAL/CHEMICAL PROPERTIES

Appearance White Powder

DIRECTIONS FOR USE

1. Turn off water supply line to toilet. **2.** Flush toilet and hold down handle. **3.** Empty entire contents of non-toxic LiquiLock into remaining water. For 3.5 gpf (gallon per flush) or larger toilets, use 2 packets of LiquiLock simultaneously into the bowl. Let LiquiLock absorb for a minimum of 4 minutes allowing water to solidify. **4.** Keeping toilet level, carefully remove as needed.

REINSTALL TOILET

1. Reconnect and turn on water supply line to the toilet. **2.** Allow toilet tank to fill with water and flush toilet. Water may fill toilet bowl. **3.** Let LiquiLock sit for a few minutes until water liquefies and flushes.

COMMON APPLICATIONS

LiquiLock by Oatey is a safe, non-toxic formulation designed to solidify water in the toilet bowl during removal of toilet from floor. Once the toilet is reinstalled, the gel re-liquefies and can be flushed down the drain.

Consult Oatey Technical Department for applications not specifically referenced above.

PRECAUTIONS

Read all cautions and directions carefully before using this product.
May be harmful if swallowed. May cause irritation. Avoid breathing vapors or dust. Use with adequate ventilation. Avoid contact with eyes, skin on clothing. Wash thoroughly after handling.

Material may be slippery when wet. Handle with care.

FIRST AID:

SKIN: Remove contaminated clothing. Wash exposed area with soap and water. If irritation persists, seek medical attention. **EYES:** Flush with plenty of water for at least 15 minutes, lifting eyelids occasionally. If irritation persists, seek medical attention. **INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. **INGESTION:** If swallowed, induce vomiting immediately after giving two glasses of water. **KEEP OUT OF REACH OF CHILDREN.**

Refer to material safety data sheet for more information. For emergency first aid help, call 1-877-740-5015.

INGREDIENTS (CAS Number)

Sodium Polyacrylate Crosslinked (9003-04-7)

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
31416	.6 oz. LiquiLock Gel – Display	24	1.5 lbs.
31417	.6 oz. LiquiLock Gel – Bulk	50	3 lbs.