

## ABS CEMENTS



#30902 shown



### ABS Medium Black Cement

- Medium-bodied black cement for use on all schedules and classes of ABS pipe and fittings up to 8" diameter with interference fit.
- For all non-pressure applications.
- Recommended application temperature 40°F to 110°F / 4°C to 43°C.
- Meets ASTM D2235, California SCAQMD 1168/316A.

| Product No. | Size   | Description                     | Ctn. Qty. |
|-------------|--------|---------------------------------|-----------|
| 30999       | 4 oz.  | ABS Medium Black                | 24        |
| 309993      | 4 oz.  | ABS Medium Black – Display Pack | 48        |
| 30889       | 8 oz.  | ABS Medium Black                | 24        |
| 308893      | 8 oz.  | ABS Medium Black – Display Pack | 36        |
| 30892       | 16 oz. | ABS Medium Black                | 24        |
| 308923      | 16 oz. | ABS Medium Black – Display Pack | 10        |
| 30902       | 32 oz. | ABS Medium Black                | 12        |
| 309023      | 32 oz. | ABS Medium Black – Display Pack | 6         |
| 30915       | Gallon | ABS Medium Black                | 6         |



#30923 shown



### ABS Special Milky Clear Cement

- Medium-bodied clear cement for use on all schedules and classes of ABS pipe and fittings up to 8" diameter with interference fit.
- Fast curing for all non-pressure applications.
- Formulated to eliminate the clean-up problems associated with black ABS cements.
- Recommended application temperature 40°F to 110°F / 4°C to 43°C.
- Meets ASTM D2235, California SCAQMD 1168/316A.

| Product No. | Size   | Description             | Ctn. Qty. |
|-------------|--------|-------------------------|-----------|
| 30922       | 16 oz. | ABS Special Milky Clear | 24        |
| 30923       | 32 oz. | ABS Special Milky Clear | 12        |
| 30924       | Gallon | ABS Special Milky Clear | 6         |



#30919 shown



### ABS Extra Special Black Cement

- Medium-bodied black cement for use on all schedules and classes of ABS pipe and fittings up to 8" diameter with interference fit.
- Formulated especially for the hot, arid climates in the Western states.
- For all non-pressure applications.
- Recommended application temperature 40°F to 110°F / 4°C to 43°C.
- Meets ASTM D2235, California SCAQMD 1168/316A.

| Product No. | Size   | Description             | Ctn. Qty. |
|-------------|--------|-------------------------|-----------|
| 30916       | 4 oz.  | ABS Extra Special Black | 24        |
| 30917       | 8 oz.  | ABS Extra Special Black | 24        |
| 30918       | 16 oz. | ABS Extra Special Black | 24        |
| 30919       | 32 oz. | ABS Extra Special Black | 12        |
| 30920       | Gallon | ABS Extra Special Black | 6         |