

Cryo-Tek[™] Original

Cryo-Tek[™]-100

.

• Pre-Mixed: Ready to use formula with 45% Virgin Propylene Glycol.

· Pre-Mixed: Ready to use formula with 55% Virgin Propylene Glycol.

- Triple Protection Inhibitor stabilizes pH to prevent corrosion, chelates, hard water minerals, and inhibits scale and sediment formation.
- Approved for use with copper, steel, iron, brass, PEX and elastomeric tubing (not for use with galvanized, CPVC, and aluminum).
- · For applications, freeze protection and specific dilutions, view submittal sheet at Oatey.com/Hercules.

Product No.	Size	Description	Ctn. Qty.
35253	Gallon	Cryo-Tek Original	6
35260	5 Gallon	Cryo-Tek Original	1
35267	55 Gallon	Cryo-Tek Original	1

#35260 shown



 Approved for use with copper, steel, iron, brass, PEX and elastomeric tubing (not for use with galvanized, CPVC, and aluminum). For application, freeze protection and specific dilutions, view submittal sheet at Oatey.com/Hercules. 				
Product No.	Size	Description	Ctn. Qty.	
35281	Gallon	Cryo-Tek-100	6	
35284	5 Gallon	Cryo-Tek-100	1	
35286	30 Gallon	Cryo-Tek-100	1	
35287	55 Gallon	Cryo-Tek-100	1	
35293	275 Gallon	Cryo-Tek-100	1	

Triple Protection Inhibitor stabilizes pH to prevent corrosion, chelates, hard water minerals, and inhibits scale and sediment formation.





#35283 shown



#35285 shown

Cryo-Tek[™]-100/AL for Aluminum

- Unique blend of antifreeze designed for use with Aluminum Heat Exchangers.
- 60% Virgin Propylene Glycol.
- Triple Protection Inhibitor package provides protection against acid corrosion, scale, sediment, and mineral deposition.
- · For application, freeze protection and specific dilutions, view submittal sheet at Oatey.com/Hercules.

Product No.	Size	Description	Ctn. Qty.
35283	5 Gallon	Cryo-Tek-100/A _L for Aluminum	1
35291	55 Gallon	Cryo-Tek-100/A⊥ for Aluminum	1



Cryo-Tek[™] AG

- Concentrated Arctic Grade solution with 95% Virgin Propylene Glycol.
- Triple Protection Inhibitor stabilizes pH to prevent corrosion, chelates, hard water minerals, and inhibits scale and sediment formation.
- Approved for use with copper, steel, iron, brass, PEX and elastomeric tubing (not for use with galvanized, CPVC, and aluminum).
- · For application, freeze protection and specific dilutions, view submittal sheet at Oatey.com/Hercules.

Product No.	Size	Description	Ctn. Qty.
35282	Gallon	Cryo-Tek AG	6
35285	5 Gallon	Cryo-Tek AG	1
35288	30 Gallon	Cryo-Tek AG	1
35289	55 Gallon	Cryo-Tek AG	1
35294	275 Gallon	Cryo-Tek AG	1



#35280 shown

Cryo-Tek[™] Solar System[™]

• Concentrated 60% Virgin Propylene Glycol.

- Triple Protection Inhibitor stabilizes pH to prevent corrosion, chelates, hard water minerals, and inhibits scale and sediment formation.
- · Approved for use with radiant tube, geothermal loops, PEX, and commonly used materials for seals and bushings.

	Product No.	Size	Description	Ctn. Qty.
	35280	5 Gallon.	Cryo-Tek Solar System	1
	35292	55 Gallon	Cryo-Tek Solar System	1