

# FLAME RESISTANT HATS & LINERS

## MODACRYLIC

### FLAME RESISTANT MULTIFUNCTIONAL GAITER

- 6 oz. Modacrylic/Tencel/Spandex Jersey Knit
- Nomex® thread
- Meets ASTM F1506
- Arc Rating: ATPV = 4.7 cal/cm<sup>2</sup>
- NFPA 70E / HRC = 1
- Flame resistant for the life of the garment

TNG-FR



### FLAME RESISTANT FULL FACE TUBE LINER

- Fits snugly over most regular brim hard hats
- 9.5 oz. Modacrylic/Cotton/Spandex Blend
  - Nomex® thread
  - Meets ASTM F1506
  - Arc Rating: ATPV = 11.6 cal/cm<sup>2</sup>
  - NFPA 70E / HRC = 2
  - Flame resistant for the life of the garment

LK910FR



### FLAME RESISTANT HARD HAT TUBE LINER

- Fits snugly over most regular brim hard hats
- 9.5 oz. Modacrylic/Cotton/Spandex Blend
  - Nomex® thread
  - Meets ASTM F1506
  - Arc Rating: ATPV = 11.6 cal/cm<sup>2</sup>
  - NFPA 70E / HRC = 2
  - Flame resistant for the life of the garment

RK900FR



## NOMEX®

### FLAME RESISTANT CAP

- 8.75 oz. Nomex® Rib Knit
- Nomex® thread
- Meets ASTM F1506
- Double layer of 7.8 cal/cm<sup>2</sup> ATPV rated knit
- NFPA 70E / HRC = 2
- Flame resistant through life of the garment



DuPont®  
Nomex.



### FLAME RESISTANT HARD HAT TUBE LINER

Fits snugly over most regular brim hard hats

- Comfortable with maximum stretch
- 8.75 oz. Nomex® Rib Knit
- Meets ASTM F1506
- Arc Rating: ATPV = 7.8 cal/cm<sup>2</sup>
- NFPA 70E / HRC = 1
- FR through life of the garment
- Made in USA

RK900NFR



DuPont®  
Nomex.



### FLAME RESISTANT FULL FACE TUBE LINER

Fits snugly over most regular brim hard hats

- Comfortable with maximum stretch
- 8.75 oz. Nomex® Rib Knit
- Meets ASTM F1506
- Arc Rating: ATPV = 7.8 cal/cm<sup>2</sup>
- NFPA 70E / HRC = 1
- Flame resistant for the life of the garment
- Made in USA

LK910NFR



DuPont®  
Nomex.



### PREMIUM FLAME RESISTANT 3-IN-1 FLEECE BALACLAVA

- Super Soft Velour inner with Jersey outer
- 5.8 oz. Nomex®/Kevlar® Blend
- Kevlar® thread
- Drawstring for adjustable/snug fit
- Hook & Loop tabs for attachment to hard hat
- Meets ASTM F1506
- Arc Rating: ATPV = 9.7 cal/cm<sup>2</sup>
- NFPA 70E / HRC = 2
- Flame resistant for the life of the garment

1070FR | 1 Layer



DuPont®  
Nomex.

