

SPECIFICATION SHEET 50-N155G



ASSURANCE® UNSUPPORTED NITRILE, FLOCK LINED WITH SUPER DIAMOND GRIP - 15 MIL

- Flock lined styles provide increased comfort and ease of donning
- Provides superior resistance to physical hazards such as cut, punchture, snag, and abrasion and many chemical hazards including solvents and oil based chemicals
- Made from component materials that comply with Federal Regulations for food contact 21CFR, 170-199
- CFIA Approved

APPLICATIONS

- Chemical processing
- Oil refining and petrochemicals
- Food processing
- Aerospace and automotive degreasing
- · Automotive assembly and painting
- Machining operations
- Metal fabrication
- · Graphic arts and printing cleanup
- Furniture manufacturing
- Electronics

TECHNICAL DATA

| MATERIAL | Nitrile / Cotton | | | | | | | |
|-------------|---|----------|----------|----------|----------|---------|--|--|
| COLOR | Green | | | | | | | |
| CUFF STYLE | Straight Cuff | | | | | | | |
| SIZES | S - XXXL | | | | | | | |
| PACKAGING | 12 pairs per dozen, 12 dozen per case | | | | | | | |
| CASE | 14.2" x 11.4" x 11.4" / 36 cm x 29 cm x 29 cm | | | | | | | |
| CASE WEIGHT | S | M | L | XL | XXL | XXXL | | |
| | 19.7 lbs | 21.0 lbs | 22.3 lbs | 23.5 lbs | 24.2 lbs | 24.8 | | |
| | 9.0 kg | 9.5 kg | 10.1 kg | 10.7 kg | 11.0 kg | 11.3 kg | | |
| C00 | Malaysia | | | | | | | |

BARCODES

| ITEM | BAG | DOZEN | CASE |
|---------------|-----|----------------|----------------|
| 50-N155G/XXXL | | 01616314044915 | 01616314044915 |
| 50-N155G/XXL | | 01616314035500 | 01616314035500 |
| 50-N155G/XL | | 01616314035494 | 01616314035494 |
| 50-N155G/L | | 01616314035463 | 01616314035463 |
| 50-N155G/M | | 01616314035470 | 01616314035470 |
| ■ 50-N155G/S | | 01616314044908 | 01616314044908 |



DIMENSIONS (in/cm)

| | | M | | XL | XXL | XXXL | | |
|---|--------------------|-------------|-------------|-------------|-------------|-------------|--|--|
| A | 13.2 / 33.5 | 13.2 / 33.5 | 13.2 / 33.5 | 13.2 / 33.5 | 13.2 / 33.5 | 13.2 / 33.5 | | |
| В | 4.0 / 10.1 | 4.4 / 11.3 | 4.8 / 12.3 | 5.4 / 13.7 | 5.7 / 14.6 | 6.1 / 15.4 | | |
| | Thickness: 0.38 mm | | | | | | | |

