



PRODUCT NUMBER: KVD18A-100

## Perfect Fit Aramid - KVD18A-100

7 gauge, standard weight, 100% Kevlar seamless knit glove, with brown dot palm coating.

### Overview

**Reference Number**

KVD18A-100

**Product Type**

Gloves

**Range**

specificprotection

**Line**

Cut resistant

**Brand**

Sperian

**Brand formerly known as**

PERFECT FIT

**Industry**

- Automotive and Part Manufacturer
- Building and Construction
- Fishing
- General Industry
- Glass Industries
- Metal steel
- Mining and Quarrying
- Ship Building
- Wood Industries

**Product Use**

Sheet Metal • Glass Handling • Canning • Automotive Sub-Assembly • Metal Stamping

## Features & Benefits

### Feature

100% Kevlar

### Benefit

Kevlar is 5x stronger than steel on an equal weight basis, and can withstand temperatures up to 900°F (480° C) without melting or degrading.

### Feature

Safety Dot Coating

### Benefit

PVC safety dot coating helps keep hands from slipping in hazardous applications.

## Technical Description

### Description

100% Kevlar seamless knit glove offers excellent cut and abrasion protection. Full PVC safety dot coating

### Product Technology

DuPont™ Kevlar® engineered fiber

### Fiber

100% Kevlar®

### Gauge

7 gauge

### Glove/liner color

Yellow

### Weight (in grams)

Standard weight

### Coating Type

PVC

### Coating Color

Brown

### Sizes

Men's, Ladies' (KVD18AL-100), Jumbo (KVD18AJ-100), and Youth (KVD18AY-100)

## ASTM F1790-97

ANSI Level Cut Resistance	Level 3
---------------------------	---------

## Packaging Label

### UOM

Pair

## Certifications

### Quality Assurance

ISO 9001 / 2000

## Photos & Images

Prod Image\_SP\_KVD18A-100

<http://www.honeywellsafety.com/assets/0/324/980/982/83f4be62-2301-40ce-bcee-d8defabbc06b.jpg>

## Maintenance

### Care Instructions

Dry cleaning is the acceptable cleaning method for gloves of KEVLAR fiber. Some differences in shrinkage, weight loss, yarn tensile strength, and color related to staining or the cleaning method may be seen, but there is no significant impact on cut resistance up to 30 cleaning cycles (without industrial use between cycles). Thirty cleaning cycles is considered to be more than can be expected because of normal wear. Chlorine bleach is not recommended for KEVLAR - chlorine will cause rapid degradation of the fiber. Wash or dry temperatures should not exceed 170° F.

**WARNING** : Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause person al injury, serious illness or death.

## Packaging

**Packaging Specs Case Box**

144

**Unit of Measure**

Pair

**Quantity per Box/Pack/Case**

144

**Quantity per Carton**

144

**Quantity for Minimum Order**

144

**Country of Origin**

China