



# AQUA-JET WATER PE-4710

Oil Creek Plastics, Inc. pressure rated pipe is manufactured from PE-4710 High Density Polyethylene and meets or exceeds all requirements of ASTM D2239, NSF Listed-Standards 14, and requirements of NSF Standard 61 and AWWA C901.

Note: 1" 160 PSI, 200 PSI, 250 PSI stocked in 100, 200, 300, 400, 500, 600 ft. lengths

SIDR-11.5 160 PSI  
SIDR-9 200 PSI  
SIDR-7 250 PSI  
available in blue

Aqua-Jet Tubing may be joined by compression type fittings specifically designed for CTS polyethylene. (Not for use with insert fittings and clamps)

## IRON PIPE SIZED (ID) NSF LISTED WATER PIPE

	SIZE	I.D.	MINIMUM WALL	WEIGHT PER 100'	MAX PSI @73.4°F	COIL LENGTHS
<b>SIDR-15 125 PSI</b>	3/4"	0.824	0.080	7.4	125	100/400
	1"	1.049	0.070	10.6	125	100/300
	1 1/4"	1.380	0.092	18.5	125	100/300
	1 1/2"	1.610	0.107	25.1	125	100/250
	2"	2.067	0.138	41.1	125	100/200
	3"	3.068	0.205	89.5	125	100/200
<b>SIDR-11.5 160 PSI</b>	3/4"	0.622	0.080	5.8	160	100/400
	1"	0.824	0.072	9.0	160	100/400
	1 1/4"	1.049	0.091	14.2	160	100/300
	1 1/2"	1.380	0.120	24.5	160	100/300
	1 3/4"	1.610	0.140	33.1	160	100/250
	2"	2.067	0.180	54.2	160	100/200
<b>SIDR-9 200 PSI</b>	3/4"	0.824	0.092	11.5	200	100/400
	1"	1.049	0.117	18.5	200	See Note
	1 1/4"	1.380	0.153	31.5	200	100/300
	1 1/2"	1.610	0.179	43.0	200	100/250
	2"	2.067	0.230	70.4	200	100/200
<b>SIDR-7 250 PSI</b>	3/4"	0.824	0.118	15.2	250	100/400
	1"	1.049	0.150	24.3	250	See Note
	1 1/4"	1.380	0.197	41.8	250	100/300
	1 1/2"	1.610	0.230	56.4	250	100/250
	2"	2.067	0.295	92.4	250	100/200

## SDR-9 AQUA-JET WATER SERVICE TUBING (CTS) COPPER TUBE SIZED (OD)

	SIZE	NOMINAL O.D.	NOMINAL I.D.	MINIMUM WALL	WEIGHT PER 100'	COIL LENGTHS
<b>SDR-9 250 PSI</b>	3/4"	0.875	0.671	0.097	10.3	100/500
	1"	1.125	0.865	0.125	16.8	100/500
	1 1/4"	1.375	1.060	0.153	25.0	100/300
	1 1/2"	1.625	1.253	0.181	35.0	100/300
	2"	2.125	1.637	0.236	59.7	100/300

All SDR-9 CTS available in Black or Blue